

Power Supply XILENCE 700 Watts PFC Active XN054

Model: XN054

Manufacturer: XILENCE

EAN: 4044953501234

Product Code: 822272

R1,445

The latest generation of Redwing power supplies combines an exciting design with modern technology and top quality. In the current revision, the power supply series has been completely revised and adapted to the demands of today's computer systems. The result not only convinces through its efficient technic, but with its modern design and high stability. The connections have been coordinated to current systems and four integrated safety circuits always ensure safe operation.

Summary: Xilence Performance A+ XN054. Total power: 700 W, AC input voltage: 200 - 240 V, AC input frequency: 50 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 45 cm, PCI Express power cable length: 50 cm. Purpose: PC, Power supply unit (PSU) form factor: ATX, Bearing technology: FDB. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Compliance certificates: RoHS, WEEE | Vendor Homepage: https://www.xilence.net/en/power-supplies/25 | Bendroji galia: 700 | AC įėjimo įtampa: 200 - 240 | AC įėjimo dažnis: 50 | Įvesties srovė: 8 | Galios koeficiento pataisos (PFC) tipas: Pasyvus | Kompleksinė galia (+3,3 V): 120 | Kompleksinė

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

galia (+12 V): 648 | Kompleksinė galia (+5V): 120 | Didžiausia išėjimo įtampa (+3,3 V): 24 | Didžiausia išėjimo įtampa (+12 V): 54 | Didžiausia išėjimo įtampa (+5 V): 18 | Didžiausia išėjimo įtampa (–12 V): 0.5 | Didžiausia išėjimo įtampa (+12 VSB): 2.5 | Maitinimo apsaugos ypatybės: Apsauga nuo per didelės įtampos/Apsauga nuo perkaitimo/Minimaliosios įtampos apsauga/Trumpasis jungimas/Viršijus galią/Viršijus nuolatinę srovę | Motininės plokštės maitinimo jungtis: 20+4 pin ATX | Motininės plokštės maitinimo kabelio ilgis: 450 | SATA elektros jungčių skaičius: 6 | Periferinė (Molex) galios jungtis (4-pin): 2 | PCI Express maitinimo jungtys (6-pin): 1 | PCI „Express“ maitinimo jungtys (6 + 2 kontaktai): 1 | PCI „Express“ galia kabelio ilgis: 500 | CPU P4 jungtis (4 kontaktai): 1 | CPU maitinimo laido ilgis: 550 | ATX maitinimo jungtis (20 + 4 kaisčiai): Taip | PCI „Express“ jungtis: Taip | Perdavimo laidu tipas: Ne modulinis | Paskirtis: PC | Maitinimo bloko (PSU) formos koeficientas: ATX | ATX versija: 2.31 | Aušinimo padengimo tipas: FDB | Produkto spalva: Juoda | Aušinimo tipas: Aktyvus | Ventiliatoriaus skersmuo: 120 | Ventiliatorių skaičius: 1 | Ventiliatoriaus vieta: Viršus | On/off mygtukas: Taip | Atitikties sertifikatai: RoHS/WEEE | Pakuotės plotis: 225 | Pakuotės gylis: 165 | Pakuotės aukštis: 100 | Paketo svoris: 1840 | Pakuotės tipas: „Box“ | Bruto svoris: 1.6 | Neto svoris: 1.2 | Vienetų skaičius vienoje siuntimo dėžėje: 10 | Vieneto plotis: 16.5 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 18 | Vieneto gylis: 23 | Vieneto aukštis: 10 | Name: CASE PSU ATX2.3.1 700W/XP700R7 XN054 XILENCE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950