



Power Supply

XILENCE 700

Watts PFC

Active XN054

Model: XN054

Manufacturer: XILENCE

EAN: 4044953501234

Product Code: 822272

R1,410

The latest generation of Redwing power supplies combines an exciting design with modern technology and top quality. In the current revision, the power supply series has been completely revised and adapted to the demands of today's computer systems. The result not only convinces through its efficient technic, but with its modern design and high stability. The connections have been coordinated to current systems and four integrated safety circuits always ensure safe operation.

Summary: Xilence Performance A+ XN054. Total power: 700 W, AC input voltage: 200 - 240 V, AC input frequency: 50 Hz. Motherboard power connector: 20+4 pin ATX, Motherboard power cable length: 45 cm, PCI Express power cable length: 50 cm. Purpose: PC, Power supply unit (PSU) form factor: ATX, Bearing technology: FDB. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Compliance certificates: RoHS, WEEE | Vendor Homepage: <https://www.xilence.net/en/power-supplies/25> | AC input frequency: 50 | AC input voltage: 200 - 240 | Combined power (+12V): 648 | Combined power (+3.3V): 120 | Combined power (+5V): 120 | Input current: 8 | Max output current

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

(+12V): 54 | Max output current (+3.3V): 24 | Max output current (+5V): 18 | Max output current (+5Vsb): 2.5 | Max output current (-12V): 0.5 | Power Factor Correction (PFC) type: Passive | Power protection features: Over current/Over power/Over voltage/Overheating/Short circuit/Under voltage | Total power: 700 | ATX power connector (20+4 pin): Yes | Cabling type: Non-Modular | CPU P4 connector (4-pin): 1 | CPU power cable length: 550 | Motherboard power cable length: 450 | Motherboard power connector: 20+4 pin ATX | Number of SATA power connectors: 6 | PCI Express connector: Yes | PCI Express power cable length: 500 | PCI Express power connectors (6+2 pin): 1 | PCI Express power connectors (6-pin): 1 | Peripheral (Molex) power connectors (4-pin): 2 | ATX version: 2.31 | Bearing technology: FDB | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 120 | Fan location: Top | Number of fans: 1 | On/off switch: Yes | Product colour: Black | Compliance certificates: RoHS/WEEE | Package depth: 165 | Package height: 100 | Package type: Box | Package weight: 1840 | Package width: 225 | Product Net Weight: 1.2 | Shipping Box Height: 18 | Unit Calculated Volume: 0.004627 | Unit Calculated Weight: 1.6 | Units per Pallet: 0 | Units per Shipping Box: 10

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950