

CASE PSU ATX2.3 350W/XN050 XILENCE

Model: XN050

Manufacturer: XILENCE

EAN: 4044953501111

Product Code: 822282

R1,112

Description

The latest generation of Redwing power supplies combines an exciting design with modern technology and top quality. In the current revision, the power supply series has been completely revised and adapted to the demands of today's computer systems. The result not only convinces through its efficient technic, but with its modern design and high stability. The connections have been coordinated to current systems and four integrated safety circuits always ensure safe operation.

Product Features

- Powerful: Optimal performance in every situation
- Whisper-Silent Cooling: 1x 120mm fan
- Reliable: Maximum stability at all time

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- The following safety features:

OVP (Over Voltage Protection)

UVP (Under Voltage Protection)

SCP (Short Circuit Protection)

OLP (Over Load Protection)

Summary: Xilence XP350R7. Total power: 350 W, AC input voltage: 200 - 240 V, Max output current (+3.3V): 14 A. Motherboard power connector: 24-pin ATX, Motherboard power cable length: 45 cm, SATA power cable length: 650 mm. Purpose: PC, Power supply unit (PSU) form factor: ATX. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm | Vendor Homepage: https://www.xilence.de/en/products/power-supplies/redwing-series/xn050.html | Bendroji galia: 350 | AC įėjimo įtampa: 200 - 240 | Didžiausia išėjimo įtampa (+3,3 V): 14 | Didžiausia išėjimo įtampa (+12 V): 20 | Didžiausia išėjimo įtampa (+5 V): 15 | Didžiausia išėjimo įtampa (–12 V): 0.5 | Didžiausia išėjimo įtampa (+12 VSB): 2 | Maitinimo apsaugos ypatybės: Apsauga nuo per didelės įtampos/Apsauga nuo perkrovos/Minimaliosios įtampos apsauga/Trumpasis jungimas | Motininės plokštės maitinimo jungtis: 24-pin ATX | Motininės plokštės maitinimo kabelio ilgis: 450 | SATA elektros jungčių skaičius: 1 | SATA maitinimo kabelio ilgis: 650 | Periferinė (Molex) galios jungtis (4-pin): 1 | Periferinio („Molex“) maitinimo kabelio ilgis: 650 | CPU P4 jungtis (4 kontaktai): 1 | ATX maitinimo jungtis (20 + 4 kaisčiai): Taip | Perdavimo laidu tipas: Ne modulinis | Paskirtis: PC | Maitinimo bloko (PSU) formos koeficientas: ATX | Produkto spalva: Juoda | Aušinimo tipas: Aktyvus | Ventiliatoriaus skersmuo: 120 | Ventiliatorių skaičius: 1 | Ventiliatoriaus vieta: Viršus | Bruto svoris: 1.54 | Neto svoris: 1.2 | Vienetų skaičius vienoje siuntimo dėžėje: 10 | Vieneto plotis: 16.5 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 18 | Vieneto gylis: 23 | Vieneto aukštis: 10 | Name: CASE PSU ATX2.3 350W/XN050 XILENCE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950