



InLine 31506E mobile device charger Universal White AC Fast charging Indoor

Model: 31506E

Manufacturer: INLINE

EAN: 4043718334445

Product Code: 870580

R1,345

65 W total power with three charging ports: Simultaneously charges smartphones, tablets and notebooks – ideal for professional multi-device environments.

Modern GaN technology for maximum efficiency: Less heat generation, compact design – ideal for mobile use.

Power Delivery 3.0 & Quickcharge 4+ compatible: Supports a wide range of fast charging protocols – perfect for current USB-C devices.

Intelligent load distribution per port: Automatic adjustment of power to connected devices – protects batteries and devices.

The InLine® USB PD power supply with 65 W power is the powerful and compact solution for demanding multi-device environments. Equipped with two USB-C ports and one USB-A port, it offers

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

maximum flexibility for simultaneous charging of modern devices.

Thanks to GaN technology, the power supply unit works particularly efficiently with low heat generation – ideal for professional continuous use. Power Delivery 3.0 and Quickcharge 4+ enable fast charging of notebooks, tablets, smartphones and accessories.

The intelligent load distribution automatically detects the connected devices and optimally adjusts the output power. A maximum total power of 65 W is achieved – even when using multiple ports simultaneously. Protective mechanisms ensure safe operation without overheating or overloading.

Input voltage: AC 100-240V

Input AC frequency: 50/60 Hz, 1.5 A

Output voltage: 3.3-20.0 V DC

Output current: max. 5.0 A

Output power: 65.0 W

Average operating efficiency: 86.67%

Efficiency at low load (10%): 76.64%

Power consumption at zero load: 0.27 W

USB-C1/C2 output: 3.3-11.0V / 3.0A or 5.0V/3.0A or 9.0V/3.0A or 12.0V/3.0A or 15.0V/3.0A or 20.0V/3.25A (65.0W max)

USB-A output: 4.5V/5.0A or 5.0V/4.5A or 9.0V/3.0A or 12.0V/2.5A or 20.0V/1.5A (30.0W max)

USB-C1+USB-C2 output: 45.0W + 18.0W (63.0W max)

USB-C1+USB-A output: 45.0W + 18.0W (63.0W max)

USB-C2+USB-A output: 5.0V/3.0A (15.0W max)

USB-C1+USB-C2+USB-A output: 45.0W + 5.0V/3.0A

USB PD 3.0 compatible, Quickcharge 4+ and backwards compatible

Dimensions: 95.7x47.2x29.4mm