



InLine 92501G wire connector Terminal block / D-Sub 9 Black



Model: 92501G

Manufacturer: INLINE

EAN: 4043718345915

Product Code: 870903

R855

Time savings during installation: Quick wiring via screw terminals for 18-26 AWG - tool-assisted with flat-head screwdriver ≤ 2.5 mm.

Stable connection thanks to knurled screw: The D-Sub-9 socket is equipped with knurled screws and ensures secure, tool-free attachment to matching connectors.

Versatile use in industry: Suitable for control technology, mechanical engineering, test setups, diagnostic purposes, and training systems.

Breakout design with pressure plate: Individual wires can be connected quickly and flexibly to the screw terminals on the rear - ideal for laboratory or field use.

High signal quality: An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of 0.8 A per pin ensure reliable signal transmission - even in continuous industrial applications

The InLine® D-Sub 9 breakout terminal block with female connector is ideal for use in test benches, laboratory environments, prototyping applications, or the commissioning of machine components.

Individual wires in the 18-26 AWG range can be securely connected via rear screw terminals with

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

pressure plate technology. Wiring is tool-assisted using a flat-blade screwdriver with a blade width $\leq$ 2.5 mm.

The socket is equipped with knurled screws (#4-40 UNC) that ensure secure, tool-free attachment to matching plugs. An EVA insulating layer provides protection when mounting on conductive surfaces. Thanks to clear terminal labeling and a robust design, the breakout adapter is ideal for test stations, control projects, and mobile service setups.

D-Sub 9 socket: Breakout design, with knurled screws (#4-40 UNC)

Connection technology: Screw terminal with pressure plate

Connection range: 18–26 AWG

Actuation: With flat-blade screwdriver $\leq$ 2.5 mm

Rated current: 0.8 A per pin

Max. operating voltage: 100 V between two signals

Insulation resistance: $\geq$ 10 M Ω @ 300 V DC

Operating temperature: -20 °C to +105 °C

Insulation layer: EVA insulation on underside

Dimensions: approx. 66.7 × 34.4 mm (L × W)

Accessories: 1× pressure plate, 2× screws