



InLine 92501I wire connector Terminal block / D-Sub 9 Black

Model: 92501I

Manufacturer: INLINE

EAN: 4043718345939

Product Code: 870905

R855

Time savings during installation: Quick wiring via screw terminals for 18–26 AWG – tool-assisted with flat-head screwdriver ≤ 2.5 mm.

Stable connection thanks to knurled screw: The D-Sub-9 connector is equipped with knurled screws (UNC #4-40) and ensures secure, tool-free attachment to matching sockets.

Versatile use in industry: Suitable for control technology, mechanical engineering, test setups, diagnostic purposes, and training systems.

Breakout design with pressure plate: Individual wires can be connected flexibly and quickly to the screw terminals on the rear – ideal for laboratory or field use.

High signal quality: An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of 0.8 A per pin ensure reliable signal transmission – even in continuous industrial use.

The InLine® D-Sub 9 breakout terminal block with connector offers a robust and flexible solution for open wiring of serial interfaces. Individual wires in the 18–26 AWG range can be connected quickly and securely via rear screw terminals with pressure plate technology. Wiring is tool-assisted with a

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

flat-head screwdriver ≤ 2.5 mm.

The D-Sub plug is equipped with knurled screws (UNC #4-40) and can be securely screwed to matching sockets without tools. An EVA insulating layer on the underside provides additional protection when mounting on conductive surfaces. Its clear terminal structure and robust design make the adapter ideal for test benches, service applications, and mobile commissioning.

D-Sub 9 plug: Breakout design, with knurled screws (#4-40 UNC)

Connection technology: Screw terminal with pressure plate

Connection range: 18-26 AWG

Actuation: With flat-blade screwdriver ≤ 2.5 mm

Rated current: 0.8 A per pin

Max. operating voltage: 100 V between two signals

Insulation resistance: ≥ 10 M Ω @ 300 V DC

Operating temperature: -20 °C to +105 °C

Insulation layer: EVA insulation on underside

Dimensions: approx. 66.7 × 34.4 mm (L × W)

Accessories: 1× pressure plate, 2× screws