



InLine 92501K wire connector Terminal block / D-Sub 9 Green



Model: 92501K

Manufacturer: INLINE

EAN: 4043718345953

Product Code: 870907

R1,062

Time savings during installation: Quick wiring via screw terminals for 14-26 AWG - tool-assisted with flat-head screwdriver ≤ 2.5 mm.

Stable connection thanks to mounting thread: The D-Sub-9 receptacle is equipped with a mounting thread (UNC #4-40) for plug locking and ensures a secure connection to matching plugs.

Versatile use in industry: Ideal for control cabinet construction, machine control, automation, and service and diagnostic environments.

DIN rail mounting for structured installations: The integrated DIN rail clip allows direct mounting in the control cabinet - space-saving and compliant with standards.

High signal quality: An insulation resistance of ≥ 10 M Ω at 300 V DC and a rated current of 0.8 A per pin ensure reliable signal transmission in professional applications.

The InLine® D-Sub 9 terminal block with female connector has been specially developed for structured installations in control cabinets or on DIN top-hat rails. The side-accessible screw terminals with pressure plate mounting enable quick wiring of single wires in the 14-26 AWG range,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

without any soldering. Assembly is tool-assisted with a flat-head screwdriver ≤ 2.5 mm.

Thanks to the mounting thread (UNC #4-40), the socket can be mechanically secured with matching connectors. The housing design with integrated DIN rail clip allows quick mounting on DIN rails. The EVA insulating layer on the underside provides additional protection when mounting on conductive surfaces.

D-Sub 9 female connector: Breakout design, with mounting thread for connector locking (UNC #4-40)

Connection technology: Screw terminal with pressure plate

Connection range: 14-26 AWG

Actuation: With flat-blade screwdriver ≤ 2.5 mm

Rated current: 0.8 A per pin

Max. operating voltage: 100 V between two signals

Insulation resistance: ≥ 10 M Ω @ 300 V DC

Operating temperature: -10 °C to +70 °C

Insulation layer: EVA insulation on underside

Mounting: Housing for direct mounting on DIN rail

Dimensions: approx. 87 × 46 × 51 mm (L × W × H)