



# InLine 92504M wire connector 6.35 mm 2-pin jack TS / Terminal block 2 terminals Black, Green



Model: 92504M

Manufacturer: INLINE

EAN: 4043718346226

Product Code: 870930

## R820

**Time savings during installation:** Quick wiring via screw terminals for 18-26 AWG – tool-assisted with flat-head screwdriver  $\leq 2.5$  mm.

**Reliable mono audio connection:** 6.35 mm jack plug (TS) with clearly assigned terminals (signal/ground) – ideal for audio technology, test setups, or control lines.

**Side terminal strip for compact installation:** Adjacent terminals in a 5.0 mm grid size enable space-saving integration – e.g., in audio racks or test environments.

**Versatile use in industry:** For analog signal wiring in audio applications, control devices, development laboratories, or measuring systems.

**High signal quality:** An insulation resistance of  $\geq 10$  M $\Omega$  at 300 V DC and a rated current of up to 1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

A per pin ensure stable and reliable signal transmission in industrial environments.

The InLine® 6.35 mm jack plug (TS, mono) on terminal block enables fast and solder-free wiring of analog signals. Ideal for audio signals, control lines, or test setups, this adapter offers an easy way to make contact – without any soldering.

The 2-pole screw terminal strip is clearly labeled: +(signal), -(ground). It supports wires in the range of 18-26 AWG and allows tool-assisted wiring with a flat-head screwdriver  $\leq 2.5$  mm. The robust housing with EVA insulation layer provides reliable protection when mounted on a conductive surface.

Thanks to its compact design, the adapter is also suitable for space-critical applications – e.g., in audio racks, test systems, or embedded projects.

**Jack connection:**6.35 mm TS jack plug (2-pin, mono)

**Number of pins / terminal assignment:**2 terminals / + (signal), – (ground)

**Connection technology:**Screw terminal with pressure plate, 5.0 mm pitch

**Connection range:**18-26 AWG

**Actuation:**With flat-blade screwdriver  $\leq 2.5$  mm

**Rated current:**1.0 A per pin

**Max. operating voltage:**100 V between two signals

**Insulation resistance:** $\geq 10$  M $\Omega$  @ 300 V DC

**Max. conductor resistance:**5 ohms

**Operating temperature:**–10 °C to +70 °C

**Insulation layer:**EVA insulation on underside