

EcoFlow 160W Foldable Solar Panel



Model: EFSOLARLIGHT160W-P-D

Manufacturer: ECOFLOW

EAN: 4895251649834

Product Code: 877571

R6,439

EcoFlow 160W Foldable Solar Panel

The EcoFlow 160W foldable solar panel is a high-performance, portable power source that allows you to conveniently charge power stations and other compatible devices in almost any conditions. With a rated power of 160 W (STC) and the use of monocrystalline TOPCon cells with an efficiency of at least 25%, the panel effectively harnesses solar energy, ensuring fast and efficient charging. The bifacial design with an efficiency of 80% $\pm$ 5% further increases the amount of energy harvested, which is particularly useful when camping, traveling in a camper, or working in the field.

High efficiency and stable operation

The panel offers an open-circuit voltage of 21.4 V and an optimal operating voltage of 18.8 V, ensuring stable performance. The optimal operating current is 8.7 A (STC), and the short-circuit current is 9.2 A, ensuring that energy is transferred efficiently and without loss. The XT60 connector guarantees broad compatibility with EcoFlow devices and other power systems equipped with a

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

compatible input.

Ready for use in harsh conditions

The IP68 rating ensures high resistance to dust and water. The operating temperature range from -40°C to 85°C allows it to be used both on hot days and in demanding weather conditions. Weighing approximately 3.8 kg and featuring a foldable design, the panel is convenient to transport and easy to store.

Foldable design for easy transport

When unfolded, the panel measures 1677 × 598 × 26 mm, offering a large active surface area for efficient solar energy harvesting. When folded, its dimensions reduce to 609 × 598 × 26 mm, making it easy to transport and store. This is a practical solution for those who need an efficient yet portable power source.

Included

- photovoltaic panel
- user manual

Manufacturer	EcoFlow
Model	EF-FOLD-160-LW
Rated power	160 W ±5 W (STC)
	177 W ±5 W (BNPI)
Open-circuit voltage	21.4 V
Short-circuit current	9.2 A (STC)
	10.2 A (BNPI)
Optimal operating voltage	18.8 V
Optimal operating current	8.7 A (STC)
	9.6 A (BNPI)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Recommended ambient temperature	-40°C to 85°C
Temperature coefficient of rated power	-0.30%/°C
Temperature coefficient of open-circuit voltage	-0.25%/°C
Temperature coefficient of short-circuit current	+0.045%/°C
Bipolarity	80% ±5%
Ingress protection	IP68
Weight	Approx. 3.8 kg
Dimensions when unfolded	1677 × 598 × 26 mm
Dimensions when folded	609 × 598 × 26 mm
Cell type	TOPCon monocrystalline silicon
Cell efficiency	≥25%
Connector type	XT60

Output power (W): 160, Type: Foldable , Rated voltage (V): 160, Rated power (W): 18.8, Rated current (A): 8.7, Built-in charge controller: Yes, Weight (kg): 3.8, GPSR Link: https://psr-assets.innpro.pl/energy/sg_energy_photovoltai_v_panels.pdf, Gross weight: 4900, Box length: 59,80, Box width: 2,60, Box height: 60,90, GARAN: <https://garan.innpro.pl/ecoflow/4895251649834>, Net weight: 3800

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950