

IMOU Home Alarm Kit 11 Ranger 2C Alarm System



Model: Alarm Kit-11-Raner2C

Manufacturer: IMOU

EAN: 6937479642742

Product Code: 877932

R4,178

IMOU Home-Alarm-Kit-11-Ranger-2C Alarm System

The comprehensive IMOU Home-Alarm-Kit-11-Ranger-2C alarm system combines the ZG2 smart gateway, motion and door/window sensors, remote controls, a siren with a volume of up to 100 dB, and the 3 MP Ranger 2C camera to create a cohesive home security ecosystem. Zigbee and Wi-Fi connectivity, a sensor range of up to 200 m in open space, and up to 2 years of battery life make the system reliable and convenient for everyday use. Integration with the app enables full control, instant notifications, and security management from anywhere.

Smart Control Center - ZG2 Gateway

The ZG2 gateway serves as the central hub of the entire system, allowing you to add, manage, and control Zigbee devices. It transmits all alarm events to the Imou cloud and directly to the user's app,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

giving you a constant overview of the situation at home. It supports up to 16 slave devices and allows you to quickly arm or disarm the system with a single button. It features a clear LED indicator showing operational status and offers flexible installation—on a desk or wall. It operates on the 2.4 GHz Wi-Fi and Zigbee 3.0 standards at temperatures ranging from -10 to 55°C.

Precise motion detection - ZP1 sensors

ZP1 motion sensors use infrared to detect human presence, working effectively even in complete darkness. The detection range is 8 m, and the viewing angle is 90°, allowing you to cover key areas of a room. Thanks to 360° adjustment and magnetic mounting, installation is quick and convenient. Low power consumption and a high-capacity CR123V battery ensure up to 2 years of operation under standard use. The sensor generates minimal data traffic, ensuring privacy and stable operation.

Door and Window Opening Monitoring - ZD1 Sensors

ZD1 sensors monitor the status of doors, windows, cabinets, or drawers, detecting when they are opened by the separation of a magnet from the sensor. The alarm is triggered at a separation of just 25 mm, allowing for a quick response to unauthorized access. The tamper-proof design and low-battery warnings enhance safety. The devices communicate over distances of up to 200 m and operate for up to 2 years on a single battery, reducing the need for maintenance.

Immediate response - ZR1 siren and convenient control - ZB1 remotes

The ZR1 alarm siren generates a sound of up to 100 dB, effectively deterring intruders and immediately alerting you to a threat. In addition to its alarm function, it also acts as a Zigbee signal booster, increasing the range and stability of communication by up to 50 m. It can be mounted on a wall or ceiling, and its functionality also includes visual alerts and notifications sent to the app. The ZB1 remotes, on the other hand, allow for quick system management without having to reach for your phone. They offer four operating modes: home arming, away arming, disarming, and SOS alarm. They support single-click, double-click, and long-press functions, allowing you to customize their operation to your needs. Thanks to low-power Zigbee technology, they operate for up to 2 years on a CR2450 battery, and their compact design allows for magnetic mounting or installation using 3M tape.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Smart Monitoring - Ranger 2C Camera

The 3 MP Ranger 2C camera works with sensors to create an advanced monitoring system. Upon detecting an event, it automatically turns toward the alarm and begins recording, while the tracking feature allows it to follow a moving object. Thanks to scene integration in the app, the camera becomes an active security element, providing visual confirmation of events.

Advanced automation and minimization of false alarms

The system utilizes multi-point correlations between sensors and the camera, enabling immediate response and intelligent operation. Triple verification—motion sensor, door sensor, and camera—significantly reduces the number of false alarms. The ability to schedule automatic arming and disarming eliminates the need for daily manual operation and enhances user convenience. All events are transmitted via the gateway to the Imou cloud and mobile app, so you receive immediate notifications of alarms. The system also allows for full management of functions, scene configuration, and remote control of the entire kit from anywhere.

Included in the kit:

- ZG2 Gateway
- ZD1 Door and Window Sensor x4
- ZB1 Remote Control x2
- ZP1 Motion Sensor x2
- ZR1 Alarm Siren
- Ranger 2C Camera
- Quick Start Guide

General

Manufacturer IMOU

Model Alarm Kit-11-Ranger2C

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

ZD1 Door and Window Sensor

Wireless Protocol	Zigbee
Transmission Power	≤10 dBm
Operating Voltage	DC 3V
Low Voltage Alarm	2.6V
Standby Current	≤10 μA
Installation Method	Wall Mount
Battery Life	2 years (20 times per day)
Transmission Frequency	2.4 GHz
Communication range	200 m (open space)
Operating temperature	From -25°C to 55°C
Operating current	≤30 mA

ZP1 motion sensor

Wireless protocol	Zigbee
Transmission power	≤15 dBm
Operating voltage	DC 3V
Low voltage alarm	2.7V
Standby current	≤15 μA
Detection range	8 m
Installation method	Wall mounting
Battery life	2 years (20 times per day)
Transmission frequency	2.4 GHz
Communication range	200 m (open space)
Battery model	CR123V
Operating temperature	From -25°C to 55°C

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Operating current ≤25 mA

Detection angle 90°

Recommended installation height 2.2 m

ZB1 remote control

Operating voltage DC 3V (1× CR2450)

Communication mode Zigbee

Operating temperature From -10°C to 50°C

Network range ≤35 m (open space)

Operating humidity ≤95% RH (non-condensing)

Battery life 2 years (may be shorter depending on conditions)

Dimensions Ø62.05 × H13.9 mm

ZR1 Alarm Siren

Operating voltage DC 12V

Standby current ≤20 µA

Operating current ≤250 mA

Operating temperature From -25°C to 55°C

Installation method Wall/ceiling

Dimensions Ø80 × 34 mm

Weight 69.8 g

ZG2 Gateway

Wireless protocol Wi-Fi IEEE 802.11 b/g/n 2.4 GHz, Zigbee 3.0

Operating voltage DC 5V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Operating temperature	-10°C to 55°C
Operating humidity	0–95% RH (non-condensing)
Installation method	Desktop / wall mount
Dimensions	68 × 68 × 24 mm

Ranger 2C Camera

Resolution	3 MP
	Automatic pan toward the event
Features	Recording upon alarm detection
	Motion tracking
Integration	Works with alarm system sensors
	Automatic response to events (scene links in the app)
Control	Imou mobile app
Operating mode	Recording triggered by sensor signals
	Automatic lens pointing toward the event location

GPSR Link: https://psr-assets.innpro.pl/smarthome/sg_smarthome_ip_cameras.pdf, Gross weight: 1370, Box length: 23,00, Box width: 20,50, Box height: 16,00, Net weight: 400