

Uni-T Flex Clamp UT-CS09D Sensor



Model: UT-CS09D

Manufacturer: UNI-T

EAN: 6935750509166

Product Code: 878371

R1,837

Uni-T Flex Clamp UT-CS09D sensor

The Uni-T Flex Clamp UT-CS09D is a flexible current sensor based on a Rogowski coil, designed for measurements in confined spaces where the use of traditional clamp meters is difficult. Thanks to its flexible design, it can comfortably wrap around wires of various diameters, and its measurement range of up to 3000 A allows it to work with high-current installations. The 45.7 cm flexible measuring cable makes it easy to adapt to various installation configurations, and when connected to compatible Uni-T meters, such as the UT206B or UT208B, results are displayed directly on the device's screen. Its robust construction, resistance to drops from a height of 1 meter, and CAT IV 600V safety rating make this model well-suited for professional measurements in demanding working conditions.

Included

- Flexible current sensor

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- BNC adapter
- 3 AAA batteries
- User manual

Specifications

Manufacturer	Uni-T
Model	UT-CS09D
Product type	Flexible current sensor (Rogowski)
AC current range	30 A / 300 A / 3000 A
Frequency response	45 Hz – 500 Hz
Flex loop length	45.7 cm
Measurement category	CAT IV 600V
Drop resistance	1 m
Ambient operating temperature range	0...50°C
Ambient storage temperature range	-20...60°C
Ambient storage humidity range	≤80% RH
Power supply	3 × 1.5 V AAA batteries
Dimensions	267 × 119.4 × 34 mm
Weight	260 g
Certifications	CE, UKCA, cETLus

GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, Gross weight: 450, Net weight: 260, Box length: 37,00, Box width: 18,50, Box height: 6,00