



Uni-T UT303D+ Infrared Thermometer



Model: UT303D+

Manufacturer: UNI-T

EAN: 6935750530399

Product Code: 878399

R2,791

Uni-T UT303D+ Infrared Thermometer

The Uni-T UT303D+ infrared thermometer is a precision device for non-contact surface temperature measurement over a wide range from -32°C to 1300°C, equipped with a dual laser for easy and accurate targeting and a fast response time of 250 ms. It offers high measurement accuracy of $\pm 1.5^{\circ}\text{C}$ or $\pm 1.5\%$ for temperatures $\geq 0^{\circ}\text{C}$, while for sub-zero temperatures, the error is calculated using the formula $\pm(1.5^{\circ}\text{C} + 0.1^{\circ}\text{C}/^{\circ}\text{C})$. The model features adjustable emissivity (0.1-1.0), a clear color EBTN display, analysis functions (MAX/MIN/AVG/DIFF), and the ability to store up to 99 measurements with date and time, making it an advanced tool for precise non-contact measurements.

Functionality and Measurement Precision

The Uni-T UT303D+ is designed for convenient and accurate operation—thanks to its 30:1 D:S ratio, it enables measurements from a greater distance while maintaining high precision. The device offers

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

visual and audible alarms, a result hold (HOLD) function, data logging, and the ability to perform scheduled measurements. Its rugged construction, resistant to drops from heights of up to 1 meter, ergonomic housing, and backlight make the device well-suited for various working conditions.

Included in the set

- Uni-T UT303D+ Infrared Thermometer
- 9V battery
- Carrying case
- User manual
- Blister packaging
- Manufacturer’s packaging

Manufacturer	Uni-T
Model	UT303D+
Temperature measurement range	-32°C ~ 1300°C
Repeatability	0.7°C or 0.7%
D:S ratio	30:1
Response time	250 ms
Emissivity adjustment	0.1 – 1.0 (5 presets)
Spectral range	8–14 μm
Laser	Dual Laser
Laser power	1 mW
Display	color EBTN, high contrast (35 x 35 mm)
Measurement modes	MAX / MIN / AVG / DIFF / HOLD
Measurement memory	up to 99 entries (with date and time)
Alarms	visual + audible
Operating temperature	0°C ~ 50°C
Storage temperature	-20°C ~ 60°C

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Operating humidity	90% RH (non-condensing)
Drop test	1 m
Power supply	9V battery
Weight	310 g
Dimensions	172 x 113.5 x 53 mm
Tripod mount	yes

GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, Gross weight: 470, Net weight: 310, Box length: 14,50, Box width: 7,50, Box height: 23,50

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950