

Uni-T UT302C+ Infrared Thermometer



Model: UT302C+

Manufacturer: UNI-T

EAN: 6935750530283

Product Code: 878403

R2,236

Uni-T UT302C+ Infrared Thermometer

The Uni-T UT302C+ infrared thermometer is an advanced device for non-contact surface temperature measurement in the range of -32°C to 1100°C , equipped with an innovative ring laser pointer that precisely marks the entire measurement area. The model offers a fast response time of 250 ms and high accuracy of $\pm 1.5^{\circ}\text{C}$ or $\pm 1.5\%$ for temperatures $\geq 0^{\circ}\text{C}$, while for sub-zero temperatures, the error is calculated using the formula $\pm(1.5^{\circ}\text{C} + 0.1^{\circ}\text{C}/^{\circ}\text{C})$. The device features adjustable emissivity (0.1–1.0), a clear color EBTN display, and analysis functions (MAX/MIN/AVG/DIFF), ensuring precise and convenient non-contact measurements.

Advanced functionality and ease of use

The Uni-T UT302C+ offers extensive capabilities thanks to features such as storage of up to 99 measurements with date and time, visual and audible alarms, and the ability to perform scheduled measurements. A 20:1 D:S ratio enables accurate measurements from a suitable distance, and the

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

built-in ring laser significantly improves control over the measurement area. The ergonomic design, backlight, and drop resistance from heights of up to 1 meter ensure comfortable use in various conditions.

Included in the set

- Uni-T UT302C+ Infrared Thermometer
- 9V battery
- Carrying case
- User manual
- Blister packaging
- Manufacturer’s packaging

Manufacturer	Uni-T
Model	UT302C+
Temperature measurement range	-32°C ~ 1100°C
Repeatability	0.7°C or 0.7%
D:S ratio	20:1
Response time	250 ms
Emissivity adjustment	0.1 – 1.0 (5 presets)
Spectral range	8–14 μm
Laser	Ring Laser
Display	color EBTN (35 x 35 mm)
Measurement modes	MAX / MIN / AVG / DIFF / HOLD
Measurement memory	up to 99 records (with date and time)
Alarms	visual + audible
Operating temperature	0°C ~ 50°C
Storage temperature	-20°C ~ 60°C
Operating humidity	90% RH (non-condensing)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Drop test	1 m
Power supply	9V battery
Weight	310 g
Dimensions	172 x 113.5 x 53 mm
Tripod mount	Yes

GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, Gross weight: 460, Net weight: 204, Box length: 21,50, Box width: 14,50, Box height: 7,00