

UNI-T UT343D paint thickness tester



Model: UT343D

Manufacturer: UNI-T

EAN: 6935750534304

Product Code: 885091

R2,949

UNI-T UT343D paint thickness tester

UNI-T UT343D is an advanced meter, designed to accurately measure the thickness of paint and other protective coatings on metallic surfaces - both steel , and aluminum. The device is distinguished by a fast measurement function, a color TFT screen, computer connectivity and a number of intelligent functions.

Wide measuring range and high precision

The UT343D measures the thickness of coatings in the range from 0 to 1,250 μm with a resolution of 0.1 μm (for the 0-99.9 μm range) and 1 μm (for values above 100 μm). The accuracy is $\pm(3\%H + 1)$ μm , allowing you to get reliable results even with very thin layers. You can perform measurements in single or continuous mode, and additional Max/Min/Avg functions help you analyze a series of measurements.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Quick test function - greater productivity

A unique feature of the UT343D is the Quick Test Mode, which allows you to define the coating thickness tolerance range. If the measured value falls within the defined range, the device signals this with a 3-color LED and an audible signal. This solution is particularly useful in the paint, sheet metal or quality control industries.

Convenient operation and additional functions

The device is equipped with a 2-inch TFT color display (320 × 240 pixels) with brightness control and automatic rotation function, which ensures comfortable operation regardless of lighting conditions and working position. In addition, a low battery indicator lets you know when the batteries need to be replaced. Measurement data can be stored in the device's memory (up to 500 groups), then transferred to a computer via USB and analyzed using dedicated software.

Included

- paint thickness tester
- micro USB cable
- batteries
- storage case

Manufacturer	UNI-T
Model	UT343D
Measuring range	0-1250 µm
Accuracy	±(3%H + 1) µm
Resolution	0.1 µm (for 0-99.9 µm); 1 µm (for 100-1250 µm)
Measurement method	Single / Continuous
Measurement mode	Max / Min / Average
Supported materials	Ferromagnetic and non-ferromagnetic metals
Display	TFT LCD 2" (320 x 240 pixels)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Quick test mode	Yes
Audible and LED alarm (3 colors)	Yes
Conversion of units	Yes
Automatic shutdown	Yes
Data memory	500 groups
USB connection	Yes
PC analysis software	Yes
Rotating screen and brightness control	Yes
Low battery indicator	Yes
Power supply	2x 1.5V AA batteries
Dimensions	153.5 × 64.5 × 41 mm
Weight	175 g

GPSR Link: https://psr-assets.innpro.pl/tools/sg_tools_measuring_tools.pdf, Gross weight: 500, Net weight: 175, Box length: 22,00, Box width: 21,00, Box height: 6,00, Information about data generation: <https://dataact.innpro.pl/uni-t/6935750534304>

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950