

Keenetic Explorer 4G (KN- 4910) AC1200 Mesh Wi-Fi 5 4G Modem Router with a 4-Port Smart Switch



Model: KN-4910-01-EU

Manufacturer: KEENETIC

EAN: 4897082922155

Product Code: 934929

R2,374

Supported protocols: EoIP, IP-IP, GRE | VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | Number of guest networks (5 GHz): 7 | Bandwidth control: Yes | Schedule access: Yes | MU-MIMO technology: Yes | Ping check: Yes | IntelliQoS: Yes | Routing table: DHCP | Antenna design: External | Routing table: Manual | Direct or cloud access via KeenDNS: Yes | USSD request support: Yes | L2TP/PPTP data rate: 95 Mbit/s | DHCP server: Yes | Number of guest networks (2.4 GHz): 7 | 4G data rate (max): 150 Mbit/s | AdGuard ad blocker: Yes | PoE/PPPoE data rate: 95 Mbit/s | Internet connection backup: Yes | Firewall: Yes | WireGuard: Yes | Cloudflare DNS: Yes | Firewall security: SPI | Parental control: Yes | Intelligent Mesh technology: Yes | Universal Plug and Play

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

(UPnP): Yes | 3G bands supported: 2100 | 3G standards: HSPA+ | System event log: Yes | 3G standards: HSDPA | 3G bands supported: 850 | Cloud-managed: Yes | Guest access: Yes | WireGuard throughput: 45 Mbit/s | SIM card type: NanoSIM | 4G standard: LTE-TDD & LTE-FDD | Dynamic DNS (DDNS): Yes | 3G/4G USB modem compatibility: No | 4G bands supported: 2100 | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | Captive portal: Yes | Switching protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | Web-based setup wizard: Yes | HTTPS security for access via KeenDNS: Yes | SSID-based VLAN assignment: Yes | Short Message Service (SMS): Yes | Mobile network generation: 4G | Traffic statistics: Yes | WPS push button: Yes | IGMP snooping: Yes | WLAN data transfer rate (first band): 300 Mbit/s | PPPoE/PPTP/L2TP pass-through: Yes | Policy-based routing: Yes | Number of users: 199 user(s) | WLAN data transfer rate (second band): 867 Mbit/s | 3G standards: WCDMA | 3G bands supported: 900 MHz | Port forwarding: Yes | SIM card slot: Yes | Port triggering: Yes | 4G bands supported: 1800 | UDP-to-HTTP proxy: Yes | DSL WAN: No | IPv4 & IPv6 features: IPv6 SSH | 4G bands supported: 2300 | WAN connection type: RJ-45, WISP | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | 4G bands supported: 1900 | 4G bands supported: 900 | DoS attack prevention: Yes | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 MHz | Command-line interface (CLI): Yes | 4G bands supported: 800 | IPv4 & IPv6 features: IPv6 Telnet | Wi-Fi Multimedia (WMM)/(WME): Yes | Web-based management: Yes | Ethernet LAN: Yes | Depth: 110 mm | Quick installation guide: Yes | Product colour: White | AC adapter included: Yes | MIMO: Yes | Quality of Service (QoS) support: Yes | Backup function: Yes | Width: 159 mm | Operating temperature (T-T): 0 - 40 °C | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | Network address translation (NAT): Yes | Ethernet LAN (RJ-45) ports: 4 | Ethernet LAN interface type: Fast Ethernet | Mobile operating systems supported: Android | Power source type: AC | Output current: 1 A | DHCP client: Yes | Antennas quantity: 4 | Processor model: MediaTek MT7628N | Product type: Tabletop router | Antenna type: External | Output voltage: 12 V | Product colour: Grey | Flash memory: 32 MB | Mobile operating systems supported: iOS | Processor frequency: 575 MHz | Weight: 236 g | Stateful Packet Inspection (SPI): Yes | Cables included: LAN (RJ-45) | Height: 29 mm | Quick start guide: Yes | Ethernet WAN: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Wi-Fi standards: Wi-Fi 4 (802.11n) | Cabling technology: 10/100Base-T(X) | LED indicators: LAN, Power, WLAN | Antenna gain level (max): 4 dBi | Internal memory: 128 MB | Number of products included: 1 pc(s) | 3G: Yes | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Processor manufacturer: MediaTek | AC input voltage: 100 - 240 V | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Antenna connector type: SMA | Built-in processor: Yes | Ethernet LAN data rates: 100 | AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 20 - 95% | Security algorithms: OWE | Modem chipset: ASR1803S | Networking standards: IEEE 802.11a | MAC address filtering: Yes | Security algorithms: WEP | Security algorithms: WPA3-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Enterprise | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11v | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | WLAN data transfer rate (max): 1200 Mbit/s | Security algorithms: WPA2-Enterprise | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK | Networking standards: IEEE 802.11k | Internal memory type: DDR2 | Security algorithms: WPA-PSK | USB port: No

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950