



HP LaserJet Pro MFP 3102fdn Printer



Model: 3G629F

Manufacturer: HEWLETT-PACKARD

EAN: 195122461751

Product Code: 936897

R5,425

Replacement cartridges: HP 139A Original Black LaserJet Toner CartridgeW1390A (~1,500 yield) HP 139X Original Black LaserJet Toner CartridgeW1390X (~4,000 yield) | Manufacturer warranty: One-year limited warranty Warranty and support options vary by product, country, and local legal requirements | Compatible operating systems: Windows 11 Windows 10 macOS 10.15 Catalina macOS 11 Big Sur macOS 12 Monterey macOS 15 Sequoia Linux | Recommended system requirements: Microsoft Windows 11 10 2 GB available hard disk space Internet connection Microsoft Internet Explorer or Edge. Apple macOS v10.15 Catalina macOS v11 Big Sur macOS v12 Monterey 2 GB HD Internet required. | Box contents: HP LaserJet Pro MFP 3102fdn Printer HP Black LaserJet Toner Introductory Cartridge (yield ~1000 pages) Setup Guide Reference Guide Regulatory Flyer Warranty Guide Power cord | Bundled software: No CD inbox (except Indonesia and China Gov) Downloadable Software from hp.com, hpsmart.com/setup, in-OS app stores. CD include HP Software Installer, Uninstaller, printer driver and other essential tools | Certification: CISPR32:2012 & CISPR32:2015 /EN55032:2012 & EN55032:2015+AC:2016 - Class B EN 61000-3-2:2014 EN 61000-3-3:2013 EN 55035:2017 FCC Title 47 CFR, Part 15 Class B/ICES-003, Issue 6 | Display diagonal: 6.86 cm (2.7") | Product colour: White | Built-in display: Yes | Package weight: 13.6 kg | Windows

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

operating systems supported: Windows 11 | AC input frequency: 50/60 Hz | Weight: 10.5 kg | Operating temperature (T-T): 15 - 32.5 °C | Power consumption (off): 0.06 W | Storage temperature (T-T): -20 - 60 °C | Operating relative humidity (H-H): 10 - 80% | Display: CGD | USB 2.0 ports quantity: 1 | Windows operating systems supported: Windows 10 | AC input voltage: 220 - 240 V | Security algorithms: SNMP | Package width: 497 mm | Ethernet LAN data rates: 10,100 Mbit/s | Power consumption (PowerSave): 0.06 W | Processor frequency: 800 MHz | Mac operating systems supported: MacOS | Cables included: AC | Carbon emissions, logistics (kg of CO2e): 3 | Duplex scanning: No | Scan speed (black): 19 ppm | Compliance certificates: GS mark | Image formats supported: JPG | Image formats supported: TIFF | Printing colours: Black | Compliance certificates: Federal Communications Commission (FCC) | Number of print cartridges: 1 | Duplex functions: Print | Maximum print size: 207 x 348 mm | Fax forwarding: Yes | Auto document feeder (ADF) input capacity: 50 sheets | Server operating systems supported: Windows Server 2008 R2 x64 | Server operating systems supported: Windows Server 2012 x64 | Total carbon footprint (kg of CO2e): 0.8 | Wi-Fi: No | Depth: 398.2 mm | Scanner type: Flatbed & ADF scanner | Compliance certificates: CE | Faxing: Mono faxing | Acoustic pressure emissions bystander (ready): 14 dB | Linux operating systems supported: Yes | Total carbon emissions, w/o use phase (kg of CO2e): 23 | Ethernet LAN: Yes | Direct printing: Yes | Scanning: Colour scanning | Server operating systems supported: Windows Server 2016 x64 | Mac operating systems supported: Mac OS X 12.0 Monterey | Printing: Mono printing | Package depth: 379 mm | Input colour depth: 24 bit | Control type: Buttons, Touch | Mac operating systems supported: Mac OS X 10.15 Catalina | Mac operating systems supported: Mac OS X 11.0 Big Sur | Built-in processor: Yes | Scan speed (colour): 8 ppm | Height: 313.2 mm | Mac operating systems supported: Mac OS X 10.15.3 Catalina | Scan technology: CIS | Auto fit function: Yes | Internal memory: 512 MB | Power consumption (sleep): 1.31 W | Fax transmission speed: 3 sec/page | Fax memory: 500 pages | Maximum scan area: 216 x 297 mm | Scan to: Software | Copier resize: 25 - 400% | Custom media length: 127 - 356 mm | Typical electricity consumption (TEC) number: Blue Angel: 0.402 kWh/week | Optical scanning resolution: 1200 x 1200 DPI | Page description languages: PCL 5c | Modem speed: 33.6 Kbit/s | Fax resolution (black): 300 x 300 DPI | Envelopes sizes: DL | Envelopes sizes: C5 | Mobile printing technologies: Mopria Print Service | Secure printing: Yes | Mobile printing technologies: Apple AirPrint | Envelopes sizes: B5 | Auto reduction: Yes | Included cartridge capacity (black): 1000 pages | Duplex printing mode: Auto | Warranty card: Yes | Optical scanning resolution (black): 1200 x 1200 ppi | Optical scanning resolution (colour): 1200 x 1200 ppi | Scan to: TWAIN | Copying: Mono copying | ISO A-series sizes (A0...A9): A4 | USB port: Yes | ISO B-series sizes (B0...B9): B5 | HP segment: Small medium business |

Total input capacity: 250 sheets | Power consumption (ready): 4.5 W | Page description languages:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

PCLmS | HP GTIN (EAN/UPC): 889894419385, 199764693914, 199764693945, 199642338074, 199764693969, 199764693983, 199764693990, 199642338098 | Power consumption (printing): 436 W | Compliance certificates: BSMI | Copy speed (black, normal quality, A4): 33 cpm | General Product Safety Regulation (GPSR) URL: https://support.hp.com/us-en/document/ish_6126692-6126777-16?openCLC=true | Compliance certificates: BIS | Maximum copy resolution: 300 x 300 DPI | Non-ISO print media sizes: L | Maximum duty cycle: 50000 pages per month | Maximum resolution: 1200 x 1200 DPI | Acoustic power emissions (ready): 32 dB | Page description languages: URF | All-In-One-multitasking: Yes | Paper tray 1 input capacity: 250 sheets | Page description languages: PDF | Maximum number of input trays: 1 | Duplex printing: Yes | Sustainability compliance: Yes | Paper tray media weight: 60 - 163 g/m² | Cartridge(s) included: Yes | Speed dialling: Yes | Sustainable technologies and materials: Forest First product | Paper tray media types: Plain paper | Compliance certificates: CCC | Recommended duty cycle: 350 - 2500 pages per month | Number of users: 10 user(s) | ISO A-series sizes (A0...A9): A6 | Compliance certificates: EAC | Auto-redialing: Yes | Cabling technology: 10/100Base-T(X) | Paper tray media types: Labels | Sound pressure level (printing): 53 dB | Non-ISO print media sizes: 16K | Paper tray media types: Glossy paper | Sound power level (printing): 6.6 dB | Carbon emissions, end-of-life (kg of CO₂e): 13 | Document formats supported: XPS | Auto document feeder (ADF): Yes | Paper tray media types: Envelopes | Document formats supported: PDF | HP Dynamic security: Yes | Package height: 490 mm | Total number of input trays: 1 | Custom media width: 76 - 216 mm | Greyscale levels: 256 | Sound pressure level (scanning): 47 dB | Maximum internal memory: 512 MB | Warm-up time: 35 s | Print speed (black, normal quality, A4/US Letter): 33 ppm | Page description languages: PWG | Carbon emissions, manufacturing (kg of CO₂e): 102 | Duplex copying: Yes | Print technology: Laser | ISO A-series sizes (A0...A9): A5 | Other operating systems supported: Linux | HP GTIN (EAN/UPC) with options: (301) 889894419385 (30A) 199764693914 (30B) 199764693945 (30N) 199642338074 (LS1) 199764693969 (LS2) 199764693983 (LS3) 199764693990 (NE1) 199642338098 | Width: 418 mm | Photo paper sizes: 10x15 cm | Paper tray media types: Cut sheet | Optical scanning resolution (ADF): 300 x 300 DPI | Paper tray media types: Postcard | Printer fonts: Scalable | Maximum input capacity: 250 sheets | Harmonized System (HS) code: 8443310000 | Custom media sizes: Width 76 to 216 mm Length 127 to 356mm | Printer fonts: TrueType | Envelopes sizes: C6 | Total output capacity: 150 sheets | Recommended humidity operating range: 30 - 70% | Maximum output capacity: 150 sheets | Fax delayed sending: Yes | Scan drivers: TWAIN | Time to first page (black, normal): 7 s | Maximum ISO A-series paper size: A4 | Time to first copy (black, normal): 6.2 s | JIS B-series sizes (B0...B9): B5 | JIS B-series sizes (B0...B9): B6 | Print resolution black: 1200 x 1200 DPI | Maximum number of copies: 999 copies | Non-ISO print media sizes: Oficio | Doesn't contain: Mercury | UNSPSC-code: 43212110 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

ISO C-series sizes (C0...C9): C6 | ISO C-series sizes (C0...C9): C5 | Recommended operating temperature range (T-T): 17.5 - 25 °C | Colour display: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950