



Asus Rack Platform (1U) AMD RS700A- E13-RS4U

Model: 90SF0451-M000N0

Manufacturer: ASUS

EAN: 4711636233217

Product Code: 937023

R95,834

Certification: BSMI, CE, CB, RCM, FCC(Class A), ISED | Mini DisplayPorts quantity: 1 | Maximum RDIMM memory: 3.07 TB | Depth: 483 mm | Number of processors supported: 2 | Number of fans: 8 fan(s) | Storage temperature (T-T): -40 - 60 °C | Ethernet LAN: Yes | Trusted Platform Module (TPM) version: 2.0 | Supported DIMM module capacities: 96GB | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 4 | Number of DIMM slots: 24 | Hot-swap HDD bays: Yes | Storage relative humidity (H-H): 20 - 90% | Integrated BMC with IPMI: Yes | Processor socket: Socket SP5 | Storage drive sizes supported: 3.5" | Storage drive sizes supported: 2.5" | Width: 821.7 mm | Number of main power supplies: 2 | Chassis type: Rack (1U) | Power supply: 2000 W | Height: 43.2 mm | Supported DIMM module capacities: 64GB | Supported memory types: DDR5-SDRAM | Supported DIMM module capacities: 32GB | Supported DIMM module capacities: 128GB | Number of storage drives supported: 4 | Number of 3.5" bays: 4 | 80 PLUS certification: 80 PLUS Titanium | PCI Express x16 (Gen 5.x) slots: 2 | Supported processors: AMD EPYC 9005 | Number of 2.5"/3.5" bays : 4 | Number of OCP3.0 ports: 2 | Operating temperature (T-T): 10 - 35 °C | Weight: 13.8 kg | Ethernet LAN (RJ-45) ports: 1 | Package weight: 16.7 kg | Trusted Platform Module (TPM): Yes | On-board graphics card memory: 64

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

MB | On-board graphics card model: Aspeed AST2600 | PCI Express slots version: 5.0 | Supported storage drive types: HDD & SSD | AC input voltage: 100 - 127/220 - 240 V | Input current: 12A / 10A | LED indicators: Yes | Supported RDIMM clock speeds: 5600 | AC input frequency: 50/60 Hz | Supported RDIMM clock speeds: 6400 MHz

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950