

NETGEAR GS728TP Managed L2/L3/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet



NETGEAR GS728TP Managed L2/L3/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey

Model: GS728TP-300EUS

Manufacturer: NETGEAR

EAN: 606449162257

Product Code: 937480

R8,170

Certification: CE, FCC Class A, RCM, ICES Class A, VCCI, KC, BSMI, UKCA | USB Type-A ports quantity: 1 | Warnings: Avoid contact of the device with liquid. | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Follow the safety guidelines for electrical current. | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Width: 440 mm | Rack mounting: Yes | Number of fans: 2 fan(s) | Operating temperature (T-T): 0 - 50 °C | Power over Ethernet (PoE): Yes | Processor manufacturer: ARM | Networking standards: IEEE 802.1D | Networking standards: IEEE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

802.1Q | Networking standards: IEEE 802.3x | Depth: 257 mm | Operating relative humidity (H-H): 0 - 90% | Noise level: 26.8 dB | Storage relative humidity (H-H): 0 - 95% | Power consumption (typical): 24 W | Power over Ethernet (PoE) power per port: 190 W | Networking standards: IEEE 802.1w | Built-in processor: Yes | Power consumption (max): 226 W | VLAN support: Yes | Power source: AC | Processor frequency: 800 MHz | Processor model: ARM Cortex-A55 | Weight: 3.78 kg | Storage temperature (T-T): -20 - 70 °C | Flash memory: 64 MB | Internal memory: 512 MB | Height: 432 mm | Product colour: Grey | Redundant fans support: Yes | DHCP features: DHCP snooping | ARP inspection: Yes | Mean time between failures (MTBF): 1751613 h | Packet buffer memory: 1.5 MB | Basic switching RJ-45 Ethernet ports quantity: 24 | Number of multicast groups filtered: 512 | Access Control List (ACL): Yes | Port mirroring: Yes | Power over Ethernet plus (PoE+) ports quantity: 24 | Access Control List (ACL) IPv4 entries: 100 | DHCP features: DHCPv6 client | Number of VLANs: 256 | Multicast support: Yes | Switching capacity: 56 Gbit/s | MAC address table: 16000 entries | IPv4 routes: 32 | Latency (1 Gbps): 4.691 µs | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Switch type: Managed | IPv6 routes: 32 | Latency (10-100 Mbps): 8.864 µs | Switch layer: L2/L3/L4 | Heat dissipation: 772.9 BTU/h | Installed SFP modules quantity: 4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950