

NETGEAR GS728TPP Managed L2/L3/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet Grey



NETGEAR GS728TPP Managed L2/L3/L4 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey

Model: GS728TPP-300EUS

Manufacturer: NETGEAR

EAN: 606449162356

Product Code: 937481

R10,374

Certification: CE, FCC Class A, RCM, ICES Class A, VCCI, KC, BSMI, UKCA | Power over Ethernet (PoE): Yes | Power consumption (typical): 26 W | Rack mounting: Yes | Width: 440 mm | Product colour: Grey | Processor manufacturer: ARM | Storage temperature (T-T): -20 - 70 °C | Internal memory: 512 MB | Operating relative humidity (H-H): 0 - 90% | Height: 432 mm | Weight: 4.11 kg | Power consumption (max): 427 W | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Mean time between failures (MTBF): 1252990 h | Operating temperature (T-T): 0 - 50 °C |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Power over Ethernet (PoE) power per port: 380 W | Storage relative humidity (H-H): 0 - 95% | VLAN support: Yes | Flash memory: 64 MB | Depth: 257 mm | Noise level: 33.3 dB | Power source: AC | Processor model: ARM Cortex-A55 | Switching capacity: 56 Gbit/s | Processor frequency: 800 MHz | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Networking standards: IEEE 802.1w | Number of fans: 2 fan(s) | Built-in processor: Yes | IPv4 routes: 32 | USB Type-A ports quantity: 1 | Warnings: Avoid contact of the device with liquid. | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Follow the safety guidelines for electrical current. | IPv6 routes: 32 | Multicast support: Yes | DHCP features: DHCP snooping | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Access Control List (ACL) IPv4 entries: 100 | ARP inspection: Yes | DHCP features: DHCPv6 client | Switch type: Managed | Redundant fans support: Yes | Power over Ethernet plus (PoE+) ports quantity: 24 | Basic switching RJ-45 Ethernet ports quantity: 24 | Number of multicast groups filtered: 512 | Installed SFP modules quantity: 4 | Access Control List (ACL): Yes | Packet buffer memory: 1.5 MB | Number of VLANs: 256 | MAC address table: 16000 entries | Switch layer: L2/L3/L4 | Latency (10-100 Mbps): 8.871 μ s | Latency (1 Gbps): 4.701 μ s

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950