

NETGEAR GS108T Managed L2 Gigabit Ethernet (10/100/1000) Grey



NETGEAR GS108T Managed L2 Gigabit Ethernet (10/100/1000) Grey

Model: GS108T-300PES

Manufacturer: NETGEAR

EAN: 606449138634

Product Code: 937483

R2,277

Certification: CE, FCC, VCCI Class B, C-Tick | Width: 158 mm | Operating temperature (T-T): 0 - 40 °C
| Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3ad | MAC address filtering:
Yes | Security algorithms: 802.1x RADIUS | Networking standards: IEEE 802.3af | Networking
standards: IEEE 802.3az | Power over Ethernet (PoE): No | Package width: 226 mm | Depth: 101 mm |
Networking standards: IEEE 802.3at | Package depth: 270 mm | Internal memory: 128 MB | Package
height: 64 mm | Package type: Box | Flash memory: 32 MB | Copper ethernet cabling technology:
10BASE-T | Copper ethernet cabling technology: 1000BASE-TX | Supported network protocols: HTTP,
HTTPS | Storage temperature (T-T): -20 - 70 °C | Copper ethernet cabling technology: 100BASE-TX |
Firmware upgradeable: Yes | Package weight: 780 g | Quality of Service (QoS) support: Yes | Height:
27 mm | Operating altitude: 0 - 3000 m | LED indicators: Power | LED indicators: Activity | AC input
voltage: 100 - 240 V | LED indicators: Link | Input current: 1.25 A | LED indicators: PoE | LED

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices
may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or
typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

indicators: Speed | AC input frequency: 50 - 60 Hz | Operating relative humidity (H-H): 0 - 95% | LED indicators: LAN | Manual: Yes | Storage relative humidity (H-H): 0 - 95% | Product colour: Grey | Products per master (outer) case: 6 pc(s) | Processor frequency: 500 MHz | Weight: 430 g | Power consumption (max): 5.5 W | MAC address auto-learning supported: Yes | Power supply included: Yes | DC input voltage: 54 V | Link aggregation: Yes | IGMP snooping: Yes | Harmonized System (HS) code: 85176990 | Mean time between failures (MTBF): 2388657 h | Switch type: Managed | Number of VLANs: 64 | Flow control support: Yes | Access Control List (ACL): Yes | Heat dissipation: 18.66 BTU/h | Basic switching RJ-45 Ethernet ports quantity: 8 | Spanning tree protocol: Yes | Broadcast storm control: Yes | Store-and-forward: Yes | DHCP features: DHCP client | Switch layer: L2 | Rate limiting: Yes | Multicast support: Yes | Stackable: No | MAC address table: 8000 entries | Master (outer) case length: 474 mm | Packet buffer memory: 0.5 MB | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Memory type: RAM | Power connector: DC-in jack | Master (outer) case gross weight: 5.49 kg | Full duplex: Yes | Switching capacity: 16 Gbit/s | Port mirroring: Yes | Jumbo frames support: Yes | Warnings: Avoid contact of the device with liquid. | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Follow the safety guidelines for electrical current. | Non-operating altitude: 0 - 3000 m | Management protocols: SNMP | Master (outer) case height: 312 mm | Master (outer) case width: 214 mm | Access Control List (ACL) IPv6 entries: 100 | Data link protocols: Ethernet, Fast Ethernet, Gigabit Ethernet | IPv4 multicast entries: 32 | Number of multicast groups filtered: 256 | Switching protocols: SNMP

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950