

NETGEAR 28-Port PoE Gigabit/10G Stackable Smart Switch (GS728TXP)



NETGEAR 28- Port PoE Gigabit/10G Stackable Smart Switch (GS728TXP)

Model: GS728TXP-300EUS

Manufacturer: NETGEAR

EAN: 606449171068

Product Code: 937484

R10,787

Switch layer: L2/L3 | Stackable: Yes | DHCP features: DHCP client | Rack mounting: Yes | Width: 440 mm | IGMP snooping: Yes | Depth: 257 mm | Noise level: 26.8 dB | Manual: Yes | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | Basic switching RJ-45 Ethernet ports quantity: 24 | Power over Ethernet (PoE): Yes | Flash memory: 64 MB | Rate limiting: Yes | Broadcast storm control: Yes | SSH/SSL support: Yes | Storage relative humidity (H-H): 0 - 95% | Operating temperature (T-T): 0 - 50 °C | Non-operating altitude: 0 - 3000 m | Link aggregation: Yes | Power consumption (typical): 748.18 W | Operating relative humidity (H-H): 0 - 95% | Built-in processor: Yes | Port mirroring: Yes | Storage temperature (T-T): -20 - 70 °C | Number of VLANs: 256 | 10G support: Yes | Height: 43.2 mm | SFP+ module slots quantity: 4 | Access Control List (ACL): Yes | VLAN support: Yes | Packet buffer memory: 16 MB | Full duplex: Yes | MAC address table: 16000 entries |

Flow control support: Yes | Networking standards: IEEE 802.3af | Networking standards: IEEE 802.3az

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

| Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | MAC address filtering: Yes | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3at | Networking standards: IEEE 802.1ab | Mean time between failures (MTBF): 1252990 h | Static route: Yes | Product colour: Black | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Access Control List (ACL) ingress: 100 | Cables included: AC | Networking standards: IEEE 802.3u | Processor frequency: 800 MHz | Weight: 3.8 kg | Networking standards: IEEE 802.1w | Number of static routes: 32 | Operating altitude: 0 - 3000 m | Spanning tree protocol: Yes | Virtual LAN features: Voice VLAN | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | Warnings: Follow the safety guidelines for electrical current.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950