

NETGEAR 52-Port PoE Gigabit/10G Stackable Smart Switch (GS752TXP)



NETGEAR 52- Port PoE Gigabit/10G Stackable Smart Switch (GS752TXP)

Model: GS752TXP-300EUS

Manufacturer: NETGEAR

EAN: 606449171181

Product Code: 937485

R17,358

Stackable: Yes | DHCP features: DHCP client | Rack mounting: Yes | Basic switching RJ-45 Ethernet ports quantity: 48 | Power supply included: Yes | Virtual LAN features: Voice VLAN | IGMP snooping: Yes | Latency (10 Gbps): 4.107 μ s | Port mirroring: Yes | Number of static routes: 32 | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | Power over Ethernet plus (PoE+) ports quantity: 48 | MAC address table: 16000 entries | Networking standards: IEEE 802.1as | Flash memory: 64 MB | Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Heat dissipation: 2944.6 BTU/h | Switch type: Managed | Rate limiting: Yes | Broadcast storm control: Yes | Networking standards: IEEE 802.3u | 10G support: Yes | SSH/SSL support: Yes | Spanning tree protocol: Yes | Total Power over Ethernet (PoE) budget: 380 W | Non-operating altitude: 0 - 3000 m | SFP+ module slots quantity: 4 | Link aggregation: Yes | Packet buffer memory: 16 MB | Static route: Yes | Storage relative humidity (H-H): 0 - 95% | Mean time between failures (MTBF): 1296949 h |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Switch layer: L2/L3/L4 | Built-in processor: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.1D | Width: 440 mm | Networking standards: IEEE 802.1x | Networking standards: IEEE 802.3i | Height: 43 mm | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1ab | Access Control List (ACL): Yes | VLAN support: Yes | Full duplex: Yes | Power over Ethernet (PoE): Yes | Flow control support: Yes | Operating altitude: 0 - 3000 m | Operating temperature (T-T): 0 - 50 °C | Operating relative humidity (H-H): 0 - 95% | Weight: 5.54 kg | Networking standards: IEEE 802.1w | Depth: 345 mm | Power consumption (max): 51 W | Product colour: Black | Power source: AC | Storage temperature (T-T): -20 - 70 °C | Noise level: 36.6 dB | Warnings: Make sure the ventilation of the equipment is not blocked. | Warnings: Avoid contact of the device with liquid. | Warnings: Follow the safety guidelines for electrical current.