

Ubiquiti UniFi Pro 24-Port PoE Managed L2/L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) 1U Silver



Model: USW-Pro-24-POE

Manufacturer: UBIQUITI

EAN: 817882027649

Product Code: 937509

R16,081

Certification: CE, FCC, IC | Weight: 4.3 kg | Quality of Service (QoS) support: Yes | Product colour: Silver | Web-based management: Yes | Networking standards: IEEE 802.3af | Redundant power supply (RPS) support: Yes | AC input voltage: 100 - 240 V | LED indicators: Link | LED indicators: Activity | Height: 43.7 mm | LED indicators: System | Networking standards: IEEE 802.3at | Reset button: Yes | Depth: 285.4 mm | LED indicators: PoE | LED indicators: Speed | Form factor: 1U | Power source: AC | Operating temperature (T-T): -5 - 40 °C | Total Power over Ethernet (PoE) budget: 400 W | Power consumption (max): 450 W | AC input frequency: 50 - 60 Hz | Operating relative humidity (H-H): 10 - 90% | Width: 442.4 mm | Rack mounting: Yes | Power over Ethernet (PoE): Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Display type: LCM | Power supply included: Yes | SFP+ module slots quantity: 2 | Broadcast storm control: Yes | Full duplex: Yes | Authentication type: IEEE 802.1x, RADIUS | Rate limiting: Yes | Number of VLANs: 1000 | Jumbo frames support: Yes | Link aggregation: Yes | Power connector: AC-in jack | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Static route: Yes | Power over Ethernet (PoE) power per port: 64 W | Harmonized System (HS) code: 85176990 | Power over Ethernet plus (PoE+) ports quantity: 16 | Switching capacity: 88 Gbit/s | System event log: Yes | IGMP snooping: Yes | VLAN support: Yes | Warnings: Follow the safety guidelines for electrical current. | DHCP features: DHCP relay | Switch layer: L2/L3 | Packet buffer memory: 2 MB | DHCP features: DHCP server | Port mirroring: Yes | DHCP features: DHCP snooping | Basic switching RJ-45 Ethernet ports quantity: 24 | Switch type: Managed | Power over Ethernet 4PPoE (PoE++) ports quantity: 8 | Warnings: Avoid contact of the device with liquid. | 10G support: Yes | Flow control support: Yes | MAC address table: 16000 entries | Warnings: Make sure the ventilation of the equipment is not blocked. | IPv4 routes: 64 | Forwarding rate: 65.472 Mpps | Throughput: 44000 Mpps | Number of power supply units: 1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950