

Ubiquiti Pro Max 16 PoE Managed L3 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Grey



Model: USW-Pro-Max-16-PoE

Manufacturer: UBIQUITI

EAN: 810084694572

Product Code: 937515

R9,583

AC input voltage: 100 - 240 V | Operating temperature (T-T): -5 - 40 °C | AC input frequency: 50/60 Hz | Housing material: Steel | VLAN support: Yes | Display type: LCM | Basic switching RJ-45 Ethernet ports quantity: 16 | Cables included: Power | Height: 43.7 mm | Depth: 160 mm | Width: 325.1 mm | Power consumption (max): 30 W | Product colour: Grey | Power supply included: Yes | LED indicators: System | Reset button: Yes | Networking standards: IEEE 802.1x | 10G support: Yes | Power over Ethernet (PoE) power per port: 15 W | Total Power over Ethernet (PoE) budget: 180 W | Switching capacity: 84 Gbit/s | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Redundant power supply (RPS) support: Yes | Weight: 2.1 kg | Mounting brackets included: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Power connector: DC-in jack | Power source: AC/DC | Operating relative humidity (H-H): 10 - 90% | Rack mounting: Yes | DHCP features: DHCPv6 relay | Manual: Yes | Jumbo frames support: Yes | DHCP features: DHCP snooping | Power over Ethernet (PoE): Yes | Warnings: Avoid contact of the device with liquid. | Warnings: Follow the safety guidelines for electrical current. | Virtual LAN features: Voice VLAN | Multicast support: Yes | Switch layer: L3 | Power over Ethernet 4PPoE (PoE++) ports quantity: 4 | Power over Ethernet plus (PoE+) ports quantity: 12 | Loop protection: Yes | Port mirroring: Yes | Throughput: 42 Gbit/s | Warnings: Make sure the ventilation of the equipment is not blocked. | Switch type: Managed | Rate limiting: Yes | SFP+ module slots quantity: 2 | Flow control support: Yes | IGMP snooping: Yes | Forwarding rate: 62.496 Mpps | Gigabit Ethernet (copper) ports quantity: 12 | Broadcast storm control: Yes | DC input voltage: 44 - 57 V | Compliance certificates: Industry Canada (IC) | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | 2.5G Ethernet (copper) ports quantity: 4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950