

**Ubiquiti USW-
PRO-MAX-48-
POE network
switch L3 2.5G
Ethernet
(100/1000/2500)
Power over
Ethernet (PoE)
Grey**



Model: USW-Pro-Max-48-PoE

Manufacturer: UBIQUITI

EAN: 810084692721

Product Code: 937516

R29,294

AC input voltage: 100 - 240 V | LED indicators: System | Reset button: Yes | Networking standards: IEEE 802.1x | Product colour: Grey | AC input frequency: 50/60 Hz | Width: 442.4 mm | Total Power over Ethernet (PoE) budget: 720 W | Rack mounting: Yes | Power over Ethernet (PoE): Yes | Operating relative humidity (H-H): 10 - 90% | Manual: Yes | Operating temperature (T-T): -5 - 40 °C | Form factor: 1U | Display type: LCM | Cables included: Power | Power source: AC | Weight: 6.2 kg | Power consumption (max): 820 W | Height: 43.7 mm | Depth: 399.6 mm | Quality of Service (QoS)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

support: Yes | Redundant power supply (RPS) support: Yes | Housing material: SGCC | 10G support: No | Virtual LAN features: Voice VLAN | DHCP features: DHCP relay | DHCP features: DHCP server | Gigabit Ethernet (copper) ports quantity: 32 | Broadcast storm control: Yes | DHCP features: DHCP guarding | Flow control support: Yes | Rate limiting: Yes | DHCP features: DHCPv6 snooping | Jumbo frames support: Yes | IGMP snooping: Yes | Power over Ethernet (PoE) power per port: 15.4 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Number of VLANs: 1000 | Rack mount kit: Yes | Power over Ethernet (PoE) voltage: 57 V | SFP+ module slots quantity: 4 | 2.5G Ethernet (copper) ports quantity: 16 | Power supply included: Yes | IPv4 routes: 12000 | Port mirroring: Yes | Switching capacity: 224 Gbit/s | Sustainability compliance: Yes | Forwarding rate: 167 Mpps | Basic switching RJ-45 Ethernet ports quantity: 48 | Static route: Yes | VLAN support: Yes | Loop protection: Yes | Power over Ethernet plus (PoE+) ports quantity: 32 | Power connector: AC-in jack | Power over Ethernet (PoE) type supported: PoE++ (4PPoE) | MAC address table: 32000 entries | Heat dissipation: 341.2 BTU/h | Packet buffer memory: 2 MB | Switch layer: L3 | Backlight display: Yes | Switch type: Managed | Power over Ethernet (PoE) type supported: PoE+ | Throughput: 112 Gbit/s | Warnings: Follow the safety guidelines for electrical current. | Warnings: Avoid contact of the device with liquid. | Power over Ethernet 4PPoE (PoE++) ports quantity: 16 | Warnings: Make sure the ventilation of the equipment is not blocked. | Compliance certificates: Federal Communications Commission (FCC) | Compliance certificates: CE | Compliance certificates: National Defense Authorization Act (NDAA) | Compliance certificates: Industry Canada (IC)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950