

**Ubiquiti UniFi
Pro XG 10 PoE
Managed L2/L3
10G Ethernet
(100/1000/10000)
Power over
Ethernet (PoE)
1U Grey**



Model: USW-Pro-XG-10-PoE

Manufacturer: UBIQUITI

EAN: 810177160137

Product Code: 937523

R16,375

10G support: Yes | Basic switching RJ-45 Ethernet ports quantity: 10 | Switching capacity: 240 Gbit/s | Power connector: AC/DC | Power supply included: Yes | IPv4 routes: 12000 | 10G Ethernet (copper) ports quantity: 10 | Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000) | Number of VLANs: 1000 | Jumbo frames support: Yes | Power over Ethernet 4PPoE (PoE++) ports quantity: 10 | IGMP snooping: Yes | MAC address table: 32000 entries | Packet buffer memory: 2 MB | DHCP features: DHCP relay | DHCP features: DHCPv6 snooping | DHCP features: DHCP server | Switch layer: L2/L3 | Stackable: Yes | Throughput: 120 Gbit/s | Static route: Yes | Power over Ethernet (PoE) type supported: PoE++ (4PPoE) | Backlight display: Yes | Broadcast storm control: Yes | Multicast

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

support: Yes | Virtual LAN features: Voice VLAN | Virtual LAN features: Interface-based VLAN | Rack mount kit: Yes | DHCP features: DHCP guarding | Port mirroring: Yes | Compliance certificates: Industry Canada (IC) | Compliance certificates: Federal Communications Commission (FCC) | Flow control support: Yes | Compliance certificates: CE | Switch type: Managed | Loop protection: Yes | Compliance certificates: National Defense Authorization Act (NDAA) | SFP+ module slots quantity: 2 | Forwarding rate: 179 Mpps | Rate limiting: Yes | Operating relative humidity (H-H): 10 - 90% | Operating temperature (T-T): -5 - 40 °C | Power consumption (max): 520 W | Rack mounting: Yes | Total Power over Ethernet (PoE) budget: 400 W | Cables included: Power | Height: 44 mm | Width: 442.4 mm | AC input frequency: 50/60 Hz | Product colour: Grey | Power over Ethernet (PoE) power per port: 15.4 W | Depth: 285 mm | Reset button: Yes | Form factor: 1U | Power source: AC/DC | Redundant power supply (RPS) support: Yes | Housing material: SGCC | Display type: LCM | LED indicators: System | VLAN support: Yes | AC input voltage: 100 - 240 V | Manual: Yes | Power over Ethernet (PoE): Yes | Quality of Service (QoS) support: Yes | Weight: 4.6 kg

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950