



PowerWalker VI 1200 LCD/FR Line-Interactive 1.2 kVA 600 W 4 AC outlet(s)

Model: VI 1200 SHL FR

Manufacturer: POWER WALKER

EAN: 4260074976533

Product Code: 937927

R3,393

Power protection features: Overload | Weight: 8.9 kg | Display type: LCD | Operating relative humidity (H-H): 0 - 90% | Output operation voltage (min): 23 V | Modem (RJ-11) ports: 1 | Audible alarm(s): Yes | Surge protection: Yes | Surge protection features: Network | Surge protection features: Telephone | Cooling type: Active | Number of batteries supported: 2 | Package width: 230 mm | Width: 139 mm | Depth: 365 mm | Power protection features: Overcharge | Operating temperature (T-T): 0 - 40 °C | Hold time (max): 4 ms | UPS topology: Line-Interactive | Ethernet LAN (RJ-45) ports: 1 | Output frequency regulation: 50 / 60 Hz | AC outlet types: Type E | USB 2.0 ports quantity: 1 | Output power: 600 W | Battery capacity: 7 Ah | Input operation voltage (max): 280 V | Form factor: Tower | Waveform: Sine | Output power capacity: 1.2 kVA | Auto-restart: Yes | Height: 195 mm | Output voltage regulation: 10% | Product colour: Black | LED indicators: Yes | AC outlets quantity: 4 AC outlet(s) | Input operation voltage (min): 170 V | Package height: 292 mm | Cold start: Yes | Battery recharge time: 6 h | Battery voltage: 12 V | Output operation voltage (max): 230 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950