

GIGABYTE P550SS power supply unit 550 W 20+4 pin ATX ATX Black



Model: GP-P550SS

Manufacturer: GIGABYTE

EAN: 4719331554187

Product Code: 938021

R1,440

ATX power connector (20+4 pin): Yes | CPU power connector (4+4 pin): Yes | Motherboard power connector: 20+4 pin ATX | Max output current (+5Vsb): 3 A | Number of SATA power connectors: 5 | Floppy drive power connector: 1 | CPU power cable length: 60 cm | Peripheral (Molex) power cable length: 500 | PCI Express connector: Yes | PCI Express power cable length: 50 cm | Max output current (-12V): 0.3 A | Floppy disk drive connector: Yes | Cooling type: Active | AC input frequency: 50/60 Hz | Product colour: Black | AC input voltage: 155-240 V | Input current: 6.3 A | Width: 150 mm | On/off switch: Yes | Peripheral (Molex) power connectors (4-pin): 3 | Height: 86 mm | Depth: 140 mm | Efficiency: 90% | Combined power (+12V): 549.6 W | ATX version: 3.0 | SATA power cable length: 500 | Max output current (+5V): 20 A | Fan diameter: 12 cm | Number of fans: 1 fan(s) | Motherboard power cable length: 60 cm | Purpose: PC | Power factor: 0.9 | Combined power (-12V): 3.6 W | Power supply unit (PSU) form factor: ATX | Combined power (+5Vsb): 15 W | 80 PLUS certification: 80 PLUS Bronze | Mean time between failures (MTBF): 100000 h | Total power: 550 W |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

PCI Express power connectors (6+2 pin): 2 | Hold time: 16 ms | Power protection features: Overheating | Power protection features: Short circuit | Power protection features: Over voltage | Fan location: Top | Harmonized System (HS) code: 84733020 | Bearing technology: HDB | Max output current (+3.3V): 20 A | Combined power (+5V): 200 W | Max output current (+12V): 45.8 A | Power protection features: Over power | Power protection features: Under voltage | Power protection features: Over current | Cabling type: Non-Modular | Power Factor Correction (PFC) type: Active | Combined power (+3.3V): 100 W

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950