



**GIGABYTE
P550SS ICE
Power Supply -
PCIe 5.0, 80
PLUS Silver,
120mm Fan,
ATX 3.0
compatible, EU
Plug**

Model: GP-P550SS ICE

Manufacturer: GIGABYTE

EAN: 4719331554910

Product Code: 938022

R1,436

Warranty period: 3 year(s) | AC input frequency: 50/60 Hz | 80 PLUS certification: 80 PLUS Silver | Mean time between failures (MTBF): 100000 h | Power protection features: Under voltage | Depth: 150 mm | Efficiency: 90% | Height: 86 mm | Package weight: 2.11 kg | Power protection features: Overheating | Floppy disk drive connector: Yes | Width: 140 mm | AC input voltage: 155-240 V | Input current: 6.3 A | Power protection features: Over power | Power protection features: Short circuit | Power protection features: Over voltage | Peripheral (Molex) power connectors (4-pin): 4 | Fan

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

diameter: 12 cm | Power protection features: Over current | Product colour: White | Number of fans: 1 fan(s) | On/off switch: Yes | Package depth: 206 mm | Package height: 117 mm | Package type: Box | Purpose: PC | Total power: 550 W | Cooling type: Active | Package width: 254 mm | Weight: 1.95 kg | PCI Express power connectors (6+2 pin): 2 | Power supply unit (PSU) form factor: ATX | Cabling type: Non-Modular | ATX power connector (20+4 pin): Yes | Power Good signal delay range: 100 - 150 ms | ATX version: 3.1 | Combined power (+12V): 549.6 W | Max output current (+5V): 20 A | Motherboard power connector: 20+4 pin ATX | Max output current (+5Vsb): 3 A | Hold time: 16 ms | Combined power (+5Vsb): 15 W | Motherboard power cable length: 60 cm | Fan location: Top | Combined power (+5V): 100 W | Max output current (+3.3V): 20 A | PCI Express connector: Yes | CPU power connector (4+4 pin): Yes | Floppy drive power connector: 2 | Bearing technology: Ball bearing | Power Factor Correction (PFC) type: Active | Number of SATA power connectors: 5 | Combined power (-12V): 3.6 W | Max output current (+12V): 45.8 A | Combined power (+3.3V): 100 W | Max output current (-12V): 0.3 A

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950