



CyberPower CP1350EPFCLCD uninterruptible power supply (UPS) Line- Interactive 1.35 kVA 780 W 6 AC outlet(s)

Model: CP1350EPFCLCD

Manufacturer: CYBERPOWER

EAN: 4711027798578

Product Code: 938114

R6,660

Noise level: 35 dB | Cooling type: Passive | Number of batteries supported: 2 | AC outlets quantity: 6
AC outlet(s) | Battery voltage: 12 V | Form factor: Tower | Ethernet LAN (RJ-45) ports: 1 | Weight:
10.9 kg | Width: 100 mm | LED indicators: Yes | USB 2.0 ports quantity: 3 | Battery capacity: 8.5 Ah |
Product colour: Black | Output power: 780 W | Number of type F outputs: 6 | Typical backup time at
full load: 4 min | Audible alarm(s): Yes | Automatic Voltage Regulation (AVR): Yes | USB port: Yes |
Modem (RJ-11) ports: 1 | Display type: LCD | Surge protection: Yes | Cabling technology:
10/100/1000Base-T(X) | Efficiency: 98.5% | Depth: 370 mm | Output power capacity: 1.35 kVA |

Power protection features: Overload | UPS topology: Line-Interactive | Typical backup time at half

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

load: 10 min | EMI/RFI noise filtering: Yes | Serial ports quantity: 1 | Output frequency: 50/60 Hz | Auto-restart: Yes | Input frequency: 50/60 Hz | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Height: 265 mm | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Keep away from sources of fire and water. | Sustainability certificates: RoHS | Surge protection features: Fax | Surge protection features: Network | Surge protection features: Telephone | Serial interface: Yes | Power plug: C14 coupler | Battery recharge time: 8 h | Nominal output voltage: 230 V | Input operation voltage (min): 165 V | Input operation voltage (max): 265 V | Surge protection features: Digital Subscriber Line (DSL) | Surge protection features: Modem | Waveform: Sine

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950