



Infosec E4 Value 1000 uninterruptible power supply (UPS) Double- conversion (Online) 1 kVA 3 AC outlet(s)

Model: INF_674178

Manufacturer: INFOSEC

EAN: 3700085674178

Product Code: 938147

R8,503

Certification: CE | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Warnings: Store away from sources of heat and open flame. | Compliance certificates: RoHS | Number of input phases: 1 | UPS topology: Double-conversion (Online) | Width: 145 mm | Input power factor: 0.99 | Input operation voltage (max): 240 V | Serial interface: Yes | Product colour: Black | Form factor: Tower | Charging current: 1 A | Efficiency: 88% | Output voltage regulation: -1 - 1% | Waveform: Pure sine | Battery voltage: 12 V | AC outlets quantity: 3 AC outlet(s) | Cold start: Yes | Cables included: Output power cable, RS-232, Input power cable | Crest factor: 3:1 | Typical backup time at full load:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

30 min | ECO mode: Yes | Audible alarm(s): Yes | Height: 282 mm | Battery capacity: 9 Ah | Input operation voltage (min): 100 V | Serial ports quantity: 1 | Battery technology: Sealed Lead Acid (VRLA) | AC outlet types: C13 coupler | Power factor: 0.8 | Number of output phases: 1 | Output frequency: 47/63 Hz | Depth: 220 mm | Output power capacity: 1 kVA | Operating temperature (T-T): 0 - 40 °C | Maximum current: 10 A | Output operation voltage (max): 240 V | Battery recharge time: 4 h | Serial interface type: RS-232 | Display type: LED | Operating relative humidity (H-H): 20 - 90% | Noise level: 50 dB | Output operation voltage (min): 100 V | Typical backup time at half load: 9 min | Input frequency: 47 - 63 Hz | Audible alarm modes: Alarm when on battery, Fault, Overload alarm, Low battery alarm | Response time: 4 ms | Weight: 8.6 kg | Manual: Yes | Output voltage Total Harmonic Distortion (THD): 6%

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950