



Ever SINLINE RT XL 3000 Line- Interactive 3 kVA 3000 W 9 AC outlet(s)



Model: W/SRTXRT-003K00/00

Manufacturer: EVER

EAN: 5907683603809

Product Code: 939766

R32,996

Storage relative humidity (H-H): 20 - 95% | Package width: 547 mm | Width: 440 mm | Cooling type: Active | Waveform: Sine | Number of phases: 1 | Height: 132 mm | Cables included: Input power cable | Output operation voltage (min): 195 V | Output power capacity: 3 kVA | Depth: 630 mm | Rubber feet: Yes | UPS topology: Line-Interactive | AC outlet types: C19 coupler | Input frequency: 50 Hz | Typical backup time at half load: 7 min | AC outlet types: C13 coupler | Maximum current: 16 A | Output operation voltage (max): 253 V | Typical backup time at full load: 3 min | International Protection (IP) code: IP20 | Power protection features: Overload | Automatic Voltage Regulation (AVR): Yes | Number of batteries supported: 8 | Cold start: Yes | Battery capacity: 7 Ah | AC outlets quantity: 9 AC outlet(s) | Battery recharge time: 4 h | Operating relative humidity (H-H): 20 - 80% | Display type: LCD | Surge protection: Yes | Manual: Yes | Form factor: Rackmount/Tower | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 1 | Package height: 247 mm | USB 2.0 ports quantity: 1 | LED indicators: Yes | Operating altitude: 0 - 1000 m | Power plug: C20 coupler | Input

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

operation voltage (min): 178 V | Input operation voltage (max): 281 V | Number of input phases: 1 | Storage temperature (T-T): 0 - 45 °C | Output power: 3000 W | Weight: 42 kg | Power protection features: Short circuit | Emergency Power Off (EPO): Yes | Product colour: Black | Quick installation guide: Yes | Number of output phases: 1 | Battery voltage: 12 V | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950