

POWER ADAPTER USB 100W/GAN FAST MRMA124 MEDIARANGE



Model: MRMA124

Manufacturer: MEDIARANGE

EAN: 4262543441832

Product Code: 943295

R1,138

Central multi-device charging solution for desktop and workstation setups

The MediaRange 100W GaN fast charging station is designed as a central charging solution for desks, workstations and home office environments. Equipped with a fixed 1.5m power cable, it provides flexible placement on desks or shelves and enables simultaneous charging of up to four devices via three USB-C ports and one USB-A port.

Advanced GaN technology for high performance and reduced heat generation

Advanced GaN (Gallium Nitride) technology allows a compact and efficient design while significantly reducing heat generation during operation. Intelligent integrated chipsets continuously monitor

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

charging power and temperature throughout the entire charging process to ensure stable, efficient and safe performance.

Support for modern fast charging standards

The charging station supports latest fast charging technologies, enabling compatible devices to be charged efficiently according to their individual power requirements. It is suitable for charging smartphones, tablets, USB-C-powered laptops, wearables and other mobile devices.

Certified safety and durable housing design

The charging station features a shock- and fire-resistant V0-rated polycarbonate housing and is Intertek GS certified, meeting high safety and quality standards for reliable everyday use in professional and private environments.

- 100W GaN fast charging station with Type-C EU-Plug and 1.5m power cable
- Supports USB-C® Power Delivery 3.0, PPS (Programmable Power Supply) and Quick Charge™ 3.0
- Three USB-C ports and one USB-A port for simultaneous charging of up to four devices
- USB-C1 and USB-C2 each support up to 100W output when used individually
- Designed for desktop, workstation and home office use as a central charging solution
- Advanced GaN technology for compact design and reduced heat generation
- Intelligent chipsets for continuous monitoring of charging power and temperature
- Overvoltage, overcharge, short-circuit and overheating protection
- Shock- and fire-resistant V0-rated polycarbonate housing
- Intertek GS certified and equipped with comprehensive protection mechanisms

Summary: MediaRange MRMA124. Charger type: Indoor, Power source type: AC, Charger compatibility: Laptop, Smartphone, Tablet. Input voltage: 100 - 240 V, Maximum output voltage: 21 V. USB Type-C ports quantity: 3, Fast charging. Cable length: 1.5 m, Product colour: White | Vendor Homepage:

https://www.mediarange.de/en/produkte/mobile_accessories/chargers_powerbanks/index.pmode/modul,det

| Charger compatibility: Laptop/Smartphone/Tablet | Charger type: Indoor | Fast charging: Yes | Fast charging technology: Power Delivery/Quick Charge 3.0 | Number of simultaneously connected

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

devices (max): 4 | Power source type: AC | Programmable power supply (PPS): Yes | USB Power Delivery (USB PD): Yes | USB Power Delivery revision: 3.0 | USB Power Delivery up to: 100 | USB Type-A ports quantity: 1 | USB Type-C ports quantity: 3 | Wireless charging: No | Cable length: 1.5 | Gallium nitride (GaN) transistors: Yes | Product colour: White | Average active efficiency: 80.57% | Efficiency (@10 %): 65.84 | Efficiency at low load (10%): Yes | Input current: 1.8 | Input frequency: 50/60 | Input voltage: 100 - 240 | Maximum output voltage: 21 | Maximum power: 100 | Minimum output voltage: 3.3 | Output current (12V): 3 | Output current (15V): 3 | Output current (20V): 5 | Output current (5V): 3 | Output current (9V): 3 | Port 1 output current: 5 | Port 2 output current: 5 | Port 3 output current: 3 | Port 4 output current: 3 | Power plug type: Type C | Depth: 40 | Height: 42 | Weight: 320 | Width: 90 | Package type: Hanging box | Quantity per pack: 1 | Model name: MRMA124 | Units per Pallet: 0 | Units per Shipping Box: 10 | Unit Calculated Volume: 0.001053 | Unit Calculated Weight: 0.41