



Asrock TRX50 WS motherboard



Model: TRX50 WS

Manufacturer: ASROCK

EAN: 4710483944529

Product Code: 945295

R13,285

Maximum internal memory: 1 TB | Wake-on-LAN ready: Yes | Supported memory module capacities: 16GB | Processor socket: Socket sTR5 | Width: 305 mm | USB 3.2 Gen 2 (3.1 Gen 2) Type-A ports quantity: 4 | Supported memory module capacities: 32GB | Supported processor sockets: Socket sTR5 | USB 2.0 connectors: 2 | Component for: PC | Processor manufacturer: AMD | Clear CMOS button: Yes | Motherboard chipset family: AMD | Number of microphone inputs: 1 | Number of M.2 (M) slots: 2 | Compatible processor series: AMD Ryzen™ 7000 Series | Supported memory types: DDR5-SDRAM | Motherboard chipset: AMD TRX50 | Ethernet LAN (RJ-45) ports: 2 | On-board graphics card: No | Motherboard form factor: EATX | Depth: 277 mm | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 2 | ATX Power connector (24-pin): Yes | ECC: Yes | Number of SATA connectors: 4 | Supported memory module capacities: 96GB | Storage temperature (T-T): 10 - 35 °C | TPM connector: Yes | Supported memory module capacities: 48GB | Supported memory module capacities: 64GB | Supported memory module capacities: 24GB | Line-out: Yes | USB 3.2 Gen 1 (3.1 Gen 1) connectors: 1 | Number of memory slots: 4 | Number of chassis fan connectors: 3 | Memory slots type: DIMM | PCI Express x16 (Gen 4.x) slots: 2 | Operating temperature (T-T): -40 - 70 °C | Number of COM connectors: 1 | Ethernet LAN: Yes | BIOS type: UEFI AMI | USB 3.2 Gen 2 (3.1 Gen 2)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Type-C ports quantity: 1 | USB 3.2 Gen 2 (3.1 Gen 2) Type-C ports quantity: 1 | Memory channels: Quad-channel | PCI Express x16 (Gen 5.x) slots: 3 | Number of antenna connectors: 2 | Number of USB 3.2 Gen 2x2 (3.1 Gen 2x2) Type-C ports : 1 | Supported storage drive interfaces: Blazing M.2 (PCIe Gen5 x4), Hyper M.2 (PCIe Gen4 x4) | SPDIF optical output: Y

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950