

IP CAMERA DAHUA IPC- HFW2849S-S-IL- 0280B



Model: IPC-HFW2849S-S-IL-0280B

Manufacturer: DAHUA

EAN: 6923172581570

Product Code: 945588

R3,373

Certification: LVD: EN62368-1 EMC: Electromagnetic Compatibility Directive 2014/30/EU FCC: 47 CFR FCC Part 15, Subpart B 2023-02-22 | Number of lenses: 1 | Lens type: Fixed focal length lens | Lens viewing angle, horizontal: 111° | Lens viewing angle, diagonal: 132° | Lens viewing angle, vertical: 58° | Warnings: The product contains electronic components do not dispose of with the normal household waste. | Warnings: Avoid direct contact with water to prevent electrical damage. | Warnings: Ensure that the product is properly installed and protected against falling. | Video compression formats: H.265+ | Mobile operating systems supported: iOS | Video compression formats: H.265 | ROM capacity: 128 MB | Ethernet interface type: Fast Ethernet | LED type: IR / White light LED | Quality of Service (QoS) support: Yes | Focal length range: 2.8 mm | Number of users: 20 user(s) | Networking standards: IEEE 802.3af | Ethernet LAN: Yes | Audio formats supported: PCM | Audio formats supported: G.711Mu | Back Light Compensation (BLC): Yes | Internal memory: 256 MB | Power consumption (Power over Ethernet (PoE)): 5.9 W | Power consumption (max): 5 W | Frame rate: 30 fps | White balance: Natural | Type: IP security camera | White balance: Manual | Operating temperature (T-T): -40 - 55 °C | Mounting type: Ceiling/wall | Storage temperature (T-T): -40 - 55 °C |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Highlight Compensation (HLC): Yes | Audio formats supported: G.711a | Sensor type: CMOS | White balance: Outdoor | Closest focusing distance: 1.5 m | Product colour: White | Noise reduction: Yes | Maximum aperture number: 1.6 | Video compression formats: M-JPEG | Minimum illumination: 0.008 lx | Video compression formats: H.264+ | Video compression formats: H.264B | Video compression formats: H.264H | Tilt angle range: 0 - 90° | Connectivity technology: Wired | White balance: Auto | Audio formats supported: G.726 | Depth: 166.2 mm | Maximum resolution: 3840 x 2160 pixels | DC output voltage: 12 | Number of cameras: 1 | Web browser: Yes | Height: 70 mm | Video motion detection: Yes | Weight: 470 g | Mobile operating systems supported: Android | Built-in HDD: No | Wide Dynamic Range (WDR): 120 dB | Video compression formats: H.264 | Bluetooth: No | Form factor: Tube/dome | White balance: Street lamp | Housing material: Metal | Web-based management: Yes | Placement supported: External / Internal | Supported graphics resolutions: 2048 x 1536 (QXGA) | Supported graphics resolutions: 3072 x 1728 | Width: 70 mm | Noise reduction technology: 3D noise reduction | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2304 x 1296 | International Protection (IP) code: IP67 | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Pan range: 0 - 360° | Supported graphics resolutions: 1280 x 720 | Supported graphics resolutions: 2880 x 1620 | Video streaming: Yes | Number of sensors: 1 | Supported graphics resolutions: 1920 x 1080 | Supported graphics resolutions: 352 x 288 | Progressive scan: Yes | Power source type: DC, PoE | Supported graphics resolutions: 3840 x 2160 | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 2688 x 1520 | Bit rate: H.264: 32 kbps-8192 kbps H.265: 12 kbps-8192 kbps | Night vision: Yes | Built-in microphone: Yes | Supported graphics resolutions: 3072 x 2048 | Wi-Fi: No | Adjustment shutter speed: Auto/Manual | Total megapixels: 8 MP | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Gain control type: Auto/Manual | Region of Interest (ROI) encoding: Yes | Camera shutter speed: 1/3 - 1/100000 s | Power consumption (typical): 2.7 W | Optical sensor size: 25.4 / 2.7 mm (1 / 2.7") | Number of illumination LEDs: 2 | Operating relative humidity (H-H): 0 - 95% | Night vision distance: 30 m

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950