

# GODOX DP600IIIIV Flash



Model: DP600IIIIV

Manufacturer: GODOX

EAN: 6952344225660

Product Code: 963785

## R7,974

### GODOX DP600IIIIV Flash

The GODOX DP600III-V flash is a high-performance 600 Ws studio flash equipped with a built-in Godox X 2.4 GHz wireless receiver, a Bowens mount, and a 30 W LED modeling light. It offers smooth flash power adjustment ranging from 1/1 to 1/64, a fast recharge time of just 1 second, and a stable color temperature of 5800 K. With a guide number of 106 and a short flash duration ranging from 1/800 to 1/2000 s, this model is ideal for portrait, product, fashion, and wedding photography. Intuitive operation, a clear LCD display, and AC 100–240 V power supply make it a versatile tool for use in a professional photography studio.

### Built-in Godox X System and Convenient Control

The DP600III-V is equipped with a built-in 2.4 GHz Godox X system receiver, which enables wireless control of the flash and makes it easy to set up complex lighting rigs. Users have access to 16 groups, 32 channels, and 99 wireless IDs, which help minimize interference and ensure stable communication between devices. Flash power can be adjusted directly from the control panel or via

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

a compatible transmitter, making it quick and convenient to change settings. The easy-to-read LCD display further simplifies operation, and the settings memory function automatically restores the last configuration when the flash is restarted.

### Precise Lighting and Versatile Applications

The GODOX DP600III-V delivers stable flash power and accurate color temperature, ensuring that consecutive photos maintain a consistent look. The flash offers as many as 61 power levels ranging from 1/1 to 1/64, allowing you to precisely adjust the lighting to the scene you’re photographing. The 30 W LED modeling light can shine at a constant brightness or in proportion to the set flash power, making it easier to assess the effect before taking the photo. A maximum recharge time of just 1 second allows for seamless operation even during intense photo shoots.

### Bowens Mount and Compatibility with Light Modifiers

Thanks to the popular Bowens mount, the light is compatible with a wide range of light modifiers, such as softboxes, beauty dishes, reflectors, spot reflectors, and other accessories that use this standard. This makes it easy to adapt the lighting to portrait, product, fashion, advertising, or wedding photography. Its sturdy construction and lightweight design—weighing just 2.8 kg, which is light for its class—make it well-suited for use both in the studio and as part of a mobile photography setup. This is the solution for those who expect high performance, ease of use, and extensive expandability for their lighting system.

### Included

- GODOX DP600III-V flash unit
- Power cord
- Flash head cover

|              |            |
|--------------|------------|
| Manufacturer | GODOX      |
| Model        | DP600III-V |
| Flash power  | 600 Ws     |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

|                              |                                                          |
|------------------------------|----------------------------------------------------------|
| <b>Guide number</b>          | 106                                                      |
| <b>Color temperature</b>     | 5800 K $\pm$ 200 K                                       |
| <b>Power adjustment</b>      | 1/1–1/64 (61 levels)                                     |
| <b>Flash duration</b>        | 1/800–1/2000 s                                           |
| <b>Maximum recharge time</b> | 1 s                                                      |
| <b>Modeling light</b>        | 30 W LED                                                 |
| <b>Control</b>               | From the flash unit or wirelessly via the Godox X system |
| <b>Wireless system</b>       | 2.4 GHz, 16 groups, 32 channels, 99 IDs                  |
| <b>Accessory mount</b>       | Bowens                                                   |
| <b>Power supply</b>          | AC 100–240 V, 50/60 Hz                                   |
| <b>Dimensions</b>            | 13 × 22 × 41 cm                                          |
| <b>Weight</b>                | 2.8 kg                                                   |

Gross weight: 4000, Net weight: 4233, Box length: 41,00, Box width: 21,50, Box height: 21,00, Set: Yes, With tripod: Yes, Adjustable intensity: Yes, GPSR Link: [https://psr-assets.innpro.pl/photo\\_and\\_accessories/sg\\_photo\\_and\\_accessories\\_photographic\\_studio.pdf](https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photographic_studio.pdf), Information about data generation: <https://dataact.innpro.pl/GODOX/6952344225660>, PPWR: <https://ppwr.innpro.pl/en/godox>

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[itworkup.co.za](https://itworkup.co.za) | [sales@itworkup.co.za](mailto:sales@itworkup.co.za) | +27 (11)541-9950