

GODOX TT350 TTL Flash for Fujifilm



Model: TT350F

Manufacturer: GODOX

EAN: 6952344211540

Product Code: 963806

R2,612

GODOX TT350F Flash for Fujifilm

The GODOX TT350F flash for Fujifilm is a compact model with a guide number of 36, designed for Fujifilm mirrorless cameras. It supports TTL auto mode, HSS flash synchronization up to 1/8000 s, and the Godox X wireless system with Master and Slave functions. It weighs just 210 g, and when the head is tilted forward, its height is only 9.5 cm, making it a great fit for compact cameras and keeping your photography setup lightweight. The set includes a diffuser, a stand, a carrying case, and the original packaging. To get started, you'll need to purchase two AA (R6) batteries, which are not included in the set.

Compact Design for Everyday Photography

The Godox TT350F was designed with mirrorless camera users in mind, so its small size complements compact camera bodies well. The flash measures 14 × 6 × 3.5 cm and weighs 210 g, so it takes up very little space in a camera bag. When mounted on the camera and with the head

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

positioned forward, it reaches a height of just 9.5 cm, which makes it more comfortable to use while shooting on location. The lightweight design makes extended use of the camera more comfortable, and the kit itself remains well-balanced.

Adjustable Head and Light Control

The flash head rotates 270° horizontally and from -7° to +90° vertically, making it easy to bounce light off walls and the ceiling. This allows you to achieve softer, more natural-looking lighting without the need for additional accessories. The built-in zoom operates within a range of 24–105 mm and can function in both automatic and manual modes, adjusting the beam angle to match the lens's focal length. The head also features a wide-angle diffuser corresponding to a focal length of approximately 15 mm and a reflector, and the kit includes an additional diffuser to soften the light.

Various operating modes and the Godox X wireless system

The flash offers a TTL mode that automatically adjusts the flash output, making it easier to shoot in varying lighting conditions. A manual mode with S1 and S2 functions is also available, as well as a Multi-strobe mode, which allows for multiple flashes during a single exposure. The built-in Godox X system transmitter allows you to control other compatible strobes as a Master unit or operate as a Slave unit controlled by an external trigger. This allows the TT350F to be used both as a standalone flash and as part of a more extensive lighting system.

HSS Synchronization and Efficient Operation

Support for HSS synchronization up to 1/8000 s allows you to use the flash even when shooting in bright daylight with fast shutter speeds. The maximum recharge time is approximately 2.2 seconds, enabling you to take consecutive shots efficiently. Powered by two AA (R6) batteries, the flash delivers a minimum of 200 full flashes per set, depending on the quality of the batteries used. Additionally, the manufacturer has equipped the flash with a micro USB port, which allows you to update the firmware and take advantage of the latest improvements.

Included in the set

- Godox TT350 flash

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Diffuser
- Stand
- Carrying case
- Manufacturer's packaging

Manufacturer	Godox
Model	TT350
Compatibility	Fujifilm cameras
Guide number	36 (ISO 100, 105 mm)
Color temperature	5600 K $\pm$ 200 K
HSS sync	up to 1/8000 s
Operating Modes	TTL, M, Multi, S1, S2, Master, Slave
Zoom	24-105 mm
Head Movement Range	-7° to +90° (vertical), 0° to 270° (horizontal)
Flash duration	1/350-1/20,000 s
Maximum recharge time	2.2 s
Display	LCD
Number of groups/channels	3/16
Triggering	hot shoe, test button, Godox X system
Power supply	2 $\times$ AA (R6), not included
Capacity	minimum 200 full flashes
Software update	micro USB
Battery pack slot	No
Dimensions	14 $\times$ 6 $\times$ 3.5 cm
Weight	210 g

Gross weight: 340, Net weight: 247, Box length: 15,00, Box width: 7,50, Box height: 8,50, Set: Yes, With tripod: Yes, Adjustable intensity: Yes, GPSR Link: https://psr-assets.innpro.pl/photo_and_accessories/sg_photo_and_accessories_photo_accessories.pdf,

Information about data generation: <https://dataact.innpro.pl/GODOX/6952344211540>, PPWR:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

