



**Hikvision Pro
Series DS-
2CD2066G2H-
IU(2.8mm)(eF)/BLACK
Indoor/Outdoor
IP Security
Bullet Camera
3200 x 1800 px
Ceiling/Wall**

Model: DS-2CD2066G2H-IU

Manufacturer: HIKVISION

EAN: 6942160480398

Product Code: 963872

R4,564

Sample rates: 8 - 48 kHz | Number of users: 32 user(s) | Identify distance: 6 m | Lens viewing angle, horizontal: 114.8° | Mounting type: Ceiling/wall | Audio formats supported: G.722.1 | Sensor type: CMOS | Recognize distance: 12 m | Audio formats supported: AAC-LC | Audio formats supported: MP2L2 | Audio formats supported: G.726 | IP address filtering: Yes | Video motion detection: Yes | Privacy masking: Yes | Built-in HDD: No | Frame rate: 30 fps | Fixed focal length: 2.8 mm | Progressive scan: Yes | Video compression formats: M-JPEG | Digest authentication: Yes | Video

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

compression formats: H.264+ | Maximum aperture number: 1 | Video compression formats: H.265+ | DC output current: 0.58 A | Video compression formats: H.264 | Intelligent Video Surveillance (IVS) system features: Human detection | Bit rate control: Constant Bit Rate (CBR)/Variable Bit Rate (VBR) | Intelligent Video Surveillance (IVS) system features: Line crossing detection | Intelligent Video Surveillance (IVS) system features: Vehicle detection | Intelligent Video Surveillance (IVS) system features: Region entrance detection | Region of Interest (ROI) encoding: Yes | Bit rate range: 8 - 320 Kbit/s | Intelligent Video Surveillance (IVS) system features: Intrusion | Image quality adjustment: Saturation | Image quality adjustment: Contrast | Video compression formats: H.265 | Lens viewing angle, vertical: 60° | Observe distance: 25 m | Day/night mode: Yes | Signal-to-Noise Ratio (SNR): 52 dB | HTTPS encryption: Yes | Noise reduction: Yes | Intelligent Video Surveillance (IVS) system features: Scene change | Infrared (IR) cut-off filter: Yes | Intelligent Video Surveillance (IVS) system features: Region exiting detection | Optical sensor size: 25.4 / 2.4 mm (1 / 2.4") | Image quality adjustment: Sharpness | Image quality adjustment: Brightness | Mirror: Yes | Password protection: Yes | Number of lenses: 1 | Heartbeat: Yes | DC output voltage: 12 | Languages support: Multi | Digital watermark: Yes | Detect distance: 64 m | Placement supported: Indoor & outdoor | Night vision: Yes | Noise reduction technology: 3D noise reduction | Dynamic range: 120 dB | Infra-red wavelength: 850 nm | Active tampering alarm: Yes | Password reset via email: Yes | Lens viewing angle, diagonal: 143.5° | Number of simultaneous live view channels: 6 channels | User access level: Administrator, Operator, User | Pixel counter: Yes | Supported graphics resolutions: 640 x 360 | Weight: 505 g | Reset button: Yes | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 2688 x 1520 | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 3200 x 1800 | Security algorithms: EAP-TLS | Product colour: Black | Networking standards: IEEE 802.3af | Connectivity technology: Wired | Bluetooth: No | Ethernet LAN (RJ-45) ports: 1 | Maximum resolution: 3200 x 1800 pixels | Networking standards: IEEE 802.1x | Security algorithms: EAP-LEAP | Supported graphics resolutions: 640 x 480 (VGA) | Security algorithms: EAP-MD5 | Video formats supported: H.264 | Compatible memory cards: MicroSDHC | Tilt angle range: 0 - 90° | Pan range: 0 - 360° | Security algorithms: TLS | Housing material: Metal | Video formats supported: H.265 | Ethernet LAN: Yes | Angle of rotation: 360° | Audio formats supported: PCM | Diameter: 7.44 cm | Number of cameras: 1 | Compatible memory cards: MicroSDXC | Audio formats supported: MP3 | Compatible memory cards: MicroSD (TransFlash) | Power consumption (max): 8.5 W | Video formats supported: M-JPEG | Audio formats supported: G.711 | Package height: 117 mm | Video formats supported: H.264+ | Package weight: 815 g | Depth: 179.2 mm | International Protection (IP) code: IP67 | Protection features: Water resistant | Storage relative humidity (H-H): 0 - 95% | Video formats supported: H.265+ | Bit rate: 32 Kbps - 16 Mbps | Wi-Fi: No |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Built-in microphone: Yes | Power source type: DC, PoE | Form factor: Bullet | Package width: 234 mm
| Minimum illumination: 0 lx | Type: IP security camera | Back Light Compensation (BLC): Yes |
Operating temperature (T-T): -30 - 60 °C | LED type: IR | Night vision distance: 40 m | Protection
features: Dust resistant | Total megapixels: 6 MP | Lens mount interface: M12 | Camera shutter
speed: 1/3 s - 1/100000 | Card reader integrated: Yes | Storage temperature (T-T): -30 - 60 °C | Wide
Dynamic Range (WDR): Yes | Highlight Compensation (HLC): Yes | Package depth: 120 mm |
Operating relative humidity (H-H): 0 - 95% | Ethernet interface type: Fast Ethernet | Audit log: Yes |
Number of Privacy masking areas: 4 | Compliance certificates: KC | Compliance certificates: REACH |
Compliance certificates: UKCA | Compliance certificates: Electromagnetic Compatibility (EMC) |
Compliance certificates: WEEE | Compliance certificates: RCM | Compliance certificates: RoHS |
Compliance certificates: CB | Compliance certificates: Low Voltage Directive (LVD)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950