



HIKVISION DS-2SE4C425MWG-E/26(F0) IP Camera



Model: DS-2SE4C425MWG-E/26(F0)

Manufacturer: HIKVISION

EAN: 6931847199630

Product Code: 966659

R11,698

Zoom speed: 3.6 s | Compatible memory cards: MicroSDXC | Compatible memory cards: MicroSD (TransFlash) | Connectivity technology: Wired | International Protection (IP) code: IP66 | Quality of Service (QoS) support: Yes | Compatible memory cards: MicroSDHC | Type: IP security camera | Height: 375 mm | Power consumption (max): 24 W | Ethernet LAN (RJ-45) ports: 1 | Operating temperature (T-T): -30 - 65 °C | Product colour: White | Operating relative humidity (H-H): 0 - 90% | Ethernet interface type: Fast Ethernet | Maximum resolution: 3632 x 1632 pixels | Bit rate: 32 Kbps - 16 Mbps | Protection features: Waterproof | Supported graphics resolutions: 352 x 288 | Card reader integrated: Yes | Wide Dynamic Range (WDR): Yes | Weight: 2.4 kg | Product colour: Black | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 352 x 240 | Supported graphics resolutions: 2560 x 1440 | Supported graphics resolutions: 960 x 432 | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 704 x 480 | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 3632 x 1632 | Supported graphics resolutions: 704 x 576 | Supported graphics resolutions: 1280 x 960 | Supported graphics resolutions: 1200 x 536 | Ethernet LAN: Yes | Tilt angle range: 0 - 90° | Power

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

source type: PoE+, DC | Audio formats supported: MP2L2 | Audio formats supported: AAC-LC | Audio formats supported: G.711 | Audio formats supported: PCM | Lens viewing angle, horizontal: 55 - 2.4° | IP address filtering: Yes | Audio formats supported: G.722.1 | Sensor type: CMOS | Optical zoom: 25x | Progressive scan: Yes | Audio formats supported: MP3 | Lens viewing angle, diagonal: 61.5 - 2.8° | Supported network protocols: IPv4/IPv6, HTTP, HTTPS, QoS,802.1x, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, DHCP, PPPoE, Bonjour | Audio formats supported: G.726 | Video compression formats: H.264 | Video compression formats: H.265 | Day/night mode: Yes | Lens viewing angle, vertical: 33 - 1.4° | Video compression formats: M-JPEG | Pan range: 360 | Region of Interest (ROI) encoding: Yes | Live view: Yes | PTZ control: Yes | Digital watermark: Yes | Camera shutter speed: 1 - 1/30000 s | Frame rate: 25 / 30 fps | Video motion detection: Yes | Privacy masking: Yes | Total megapixels: 6 MP | Zoom capability: Yes | Alarm input channels: 1 | Alarm input/output: Yes | Highlight Compensation (HLC): Yes | Dynamic range: 120 dB | Maximum memory card size: 256 GB | Number of users: 32 user(s) | Number of cameras: 1 | Preset programs quantity: 300 | Built-in speaker(s): Yes | DC output voltage: 12 | Minimum illumination: 0 lx | Auto focus: Yes | Number of simultaneous live view channels: 20 channels | Digital zoom: 16x | Password protection: Yes | Product diameter: 166 mm | Client interoperability: iVMS-4200,Hik-Connect | Alarm output channels: 1 | Night vision: Yes | LED type: IR | Mounting type: Ceiling | Placement supported: Outdoor | Automatic Network Replenishment (ANR): Yes | PTZ status display: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950