



CyberPower BR700ELCD-FR uninterruptible power supply (UPS) Line- Interactive 0.7 kVA 420 W 8 AC outlet(s)

Model: BR700ELCD-FR

Manufacturer: CYBERPOWER

EAN: 4712856271225

Product Code: 967103

R3,094

Certification: CE | EMI/RFI noise filtering: Yes | Power protection features: Overload | Output power capacity: 0.7 kVA | UPS topology: Line-Interactive | Depth: 288 mm | Response time: 4 ms | Weight: 5.3 kg | AC outlet types: Type E | Display type: LCD | Surge protection: Yes | Ethernet LAN (RJ-45) ports: 2 | Cold start: Yes | USB port: Yes | Waveform: Sine | Width: 166 mm | Output frequency: 50/60 Hz | Surge protection features: Modem | Height: 118 mm | Battery technology: Sealed Lead Acid (VRLA) | Housing material: Plastic | Audible alarm(s): Yes | Warnings: Do not disassemble the unit housing, there may be a risk of electric shock. | Storage relative humidity (H-H): 0 - 90% |

Compliance certificates: RoHS | USB 2.0 ports quantity: 1 | Input operation voltage (max): 290 V |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

Typical backup time at full load: 2 min | Operating altitude: 0 - 3000 m | Input operation voltage (min): 165 V | LED indicators: Yes | Operating relative humidity (H-H): 0 - 90% | Operating temperature (T-T): 0 - 40 °C | Cable length: 1.5 m | AC outlets quantity: 8 AC outlet(s) | Surge energy rating: 125 J | Output power: 420 W | Audible alarm modes: Alarm when on battery, Fault, Low battery alarm, Overload alarm | Storage temperature (T-T): -20 - 50 °C | Product colour: Black | Input frequency: 50/60 Hz | Typical backup time at half load: 6 min | Automatic Voltage Regulation (AVR): Yes | Battery recharge time: 8 h | Non-operating altitude: 0 - 3000 m | Modem (RJ-11) ports: 2 | Form factor: Compact | Surge protection features: Digital Subscriber Line (DSL) | Surge protection features: Fax | Warnings: Use the appliance in well-ventilated areas to avoid overheating. | Surge protection features: Network | Surge protection features: Telephone | Warnings: Keep away from sources of fire and water.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950