

ANCEL L5000 PRO Diagnostic Leak Detector for Automotive Systems



Model: L5000 PRO

Manufacturer: ANCEL

EAN: 6978281190588

Product Code: 967853

R7,306

ANCEL L5000 PRO Diagnostic Leak Detector for Automotive Systems

The ANCEL L5000 PRO is an advanced leak detector designed to test automotive systems using air and smoke. It enables quick leak detection by introducing smoke into the system under test and operating in various modes—from low pressure (0.5 psi) to high pressure (20 psi). The device also supports pressure decay testing at a specified pressure and vacuum leak testing, which expands diagnostic capabilities when working with various vehicle systems.

Wide range of applications in vehicle system diagnostics

The detector is designed to test the tightness of many automotive systems. For example, you can use it to diagnose the EVAP system, the air intake system, the exhaust system, the intercooler—

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

system, the oil circuit, and water lines. The L5000 PRO model allows you to simulate the appropriate operating pressure conditions and quickly locate the source of a leak using visible smoke.

Various pressure modes and available tests

The ANCEL L5000 PRO supports a low-pressure mode of 0.5 psi, a high-pressure mode of 20 psi, and a linear mode with adjustable output pressure ranging from 0.5 to 20 psi. The device offers air leak testing, smoke leak testing, pressure decay testing, and vacuum leak testing. With a pressure resolution of 0.001 of the selected unit and a flow resolution of 0.01 l/min, the user can more precisely control the test process and analyze diagnostic results.

Intuitive control panel and self-diagnostics

The device is equipped with a control panel featuring an LCD screen and 4 function buttons. This allows you to conveniently select operating modes and adjust test parameters. Additionally, a self-test function is available, which enables the device to perform self-diagnostics in the event of operational issues.

Designed for workshop use

The L5000 PRO model is compatible with 12 V automotive batteries and offers a flow rate of less than 8 l/min. It also comes with a power cord and a smoke hose—each 2.5 m long—which makes it easier to work around the vehicle. You also have a Velcro strap for storing them and a hook for hanging the unit.

A set of adapters for various applications

The kit includes numerous adapters and accessories designed to work with various vehicle systems. In the package, you'll find, among other things, adapter cones for holes with diameters of 25–55 mm, an EVAP service port adapter, a set of plugs, and an intake bladder designed for holes with diameters of 25–140 mm.

Included in the kit

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Diagnostic leak detector
- Power cord
- Supply hose
- Hook
- Funnel
- Intake bladder
- Replacement parts for the intake bladder
- Adapter cone
- Set of adapter cones
- Set of locking cones
- EVAP adapter
- EVAP removal tool
- Set of plugs

Manufacturer	ANCEL
Model	L5000 PRO
Device type	Diagnostic leak detector for automotive systems
Display	3.5-inch screen
Power supply	12 V DC (car battery), 8 A
Output pressure	Constant low (0.5 psi) / high (20 psi) pressure modes and a linear, adjustable output pressure mode ranging from 0.5 to 20 psi
Flow rate	8 l/min
Power cord length	2.5 m
Smoke hose length	2.5 m
Pressure resolution	0.001 of the selected unit
Flow rate resolution	0.01 l/min

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Supported functions	Air leak test, smoke leak test, pressure distribution test, vacuum leak test, device self-diagnostics
Air source	Built-in pump
Languages	Chinese, English, Spanish, Portuguese, German, French, Italian
Dimensions	164 x 168 x 245 mm
Weight	2.4 kg

GPSR Link: https://psr-assets.innpro.pl/car_accessories/sg_car_accessories_diagnostic_tools.pdf,

Gross weight: 4290, Box length: 32,00, Box width: 21,00, Box height: 26,00, Net weight: 2560,

Information about data generation: <https://dataact.innpro.pl/ANCEL/6978281190588>, PPWR:

<https://ppwr.innpro.pl/ancel>, Last delivery: 14.09.2026

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950