

Power Supply TECNOWARE ATX PC 180 - 264 V 750 W FAL751FSP12

Model: FAL751FSP12

Manufacturer: TECNOWARE

EAN: 8026475179951

Product Code: 985788

R1,531

Internal power supply for personal computer, 750W power, input voltage 230 Vac, 50/60 Hz, conforms to ATX 12V v.2.31 specifications, main switch, surge protection, overload protection, short circuit protection, high MTBF, high reliability, quiet operation, 12 cm silent fan, temperature control of the fan speed, Flat type connection cables from 500mm to 800mm, 1 x 20+4-pin connector, 1 x 12V 4+4-pin connector, 2 x 6+2 PCI-E connector, 2 x molex connectors, 4 x Sata connector, dimensions 150x140x86 mm, weight 1.0 Kg, black color, CE certification, Rohs.

- Internal Power Supply for Computers
- High Efficiency (>85%) and High Operation Noise
- Active PFC >0.9
- Dimensions: 140x86x150 mm (WxHxD)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- Input voltage 230 Vac 50Hz
- Temperature control of the fan speed
- Flat connection cables from 500mm to 800mm
- Surge protection
- Overload protection
- Short circuit protection

Summary: Tecnoware FAL751FSP12. Total power: 750 W, AC input voltage: 180 - 264 V, AC input frequency: 47 - 63 Hz. Motherboard power connector: 24-pin ATX. Purpose: PC, Power supply unit (PSU) form factor: ATX. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 150 mm, Depth: 140 mm, Height: 86 mm | Vendor Homepage: https://www.tecnoware.com/en-US/Dettaglio/Articolo/850 | Bendroji galia: 750 | AC įėjimo įtampa: 180 - 264 | AC įėjimo dažnis: 47 - 63 | Galios koeficiento pataisos (PFC) tipas: Aktyvus | Didžiausia išėjimo įtampa (+3,3 V): 26 | Didžiausia išėjimo įtampa (+12 V): 52 | Didžiausia išėjimo įtampa (+5 V): 26 | Didžiausia išėjimo įtampa (–12 V): 0.8 | Didžiausia išėjimo įtampa (+12 VSB): 2.5 | Efektyvumas: 85 | Maitinimo apsaugos ypatybės: Apsauga nuo perkrovos/Apsauga nuo viršįtampių/Trumpasis jungimas | Motininės plokštės maitinimo jungtis: 24-pin ATX | SATA elektros jungčių skaičius: 4 | Periferinė (Molex) galios jungtis (4-pin): 2 | PCI „Express“ maitinimo jungtys (6 + 2 kontaktai): 2 | CPU maitinimo jungtis (4 + 4 kaisčiai): Taip | Sertifikatas 80 PLUS: Ne | Paskirtis: PC | Maitinimo bloko (PSU) formos koeficientas: ATX | ATX versija: 2.31 | Produkto spalva: Juoda | Aušinimo tipas: Aktyvus | Ventiliatoriaus skersmuo: 120 | Ventiliatorių skaičius: 1 | On/off mygtukas: Taip | Darbo temperatūros diapazonas (TT): 0 - 40 | Sandėliavimo temperatūros norma (T-T): -15 - 40 | Plotis: 150 | Ilgis: 140 | Aukštis: 86 | Svoris: 1000 | Bruto svoris: 1.34 | Neto svoris: 1 | Vienetų skaičius vienoje siuntimo dėžėje: 8 | Vieneto plotis: 16 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 18 | Vieneto gylis: 22 | Vieneto aukštis: 9.5 | Name: CASE PSU ATX 750W/FAL751FSP12 TECNOWARE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950