

Power Supply TECNOWARE ATX PC 180 - 264 V 650 W FAL651FSP12



Model: FAL651FSP12

Manufacturer: TECNOWARE

EAN: 8026475179944

Product Code: 985792

R1,279

Internal power supply for personal computer, power 650W, input voltage 230 Vac, 50/60 Hz, conforms to ATX 12V v.2.31 specifications, main switch, surge protection, overload protection, short circuit protection, high MTBF, high reliability, quiet operation, 12 cm silent fan, temperature control of fan speed, Flat type connection cables from 500mm to 800mm, 1 x 20+4-pin connector, 1 x 12V 4+4-pin connector, 1 x 6+2 PCI-E connector, 2 x Molex connectors, 4 x Sata connector, dimensions 150x140x86 mm, weight 1.0 Kg, black color, CE certification, RoHS.

- Internal Power Supply for Computers
- High Efficiency (>85%) and High Operation Noise
- Active PFC >0.9
- Dimensions: 140x86x150 mm (WxHxD)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

- Input voltage 230 Vac 50Hz
- Temperature control of the fan speed
- Flat connection cables from 500mm to 800mm
- Surge protection
- Overload protection
- Short circuit protection

Summary: Tecnoware FAL651FSP12. Total power: 650 W, AC input voltage: 180 - 264 V, AC input frequency: 47 - 63 Hz. Motherboard power connector: 24-pin ATX. Purpose: PC, Power supply unit (PSU) form factor: ATX. Product colour: Black, Cooling type: Active, Fan diameter: 12 cm. Width: 150 mm, Depth: 140 mm, Height: 86 mm | Vendor Homepage: <https://www.tecnoware.com/en-US/Dettaglio/Articolo/849> | AC input frequency: 47 - 63 | AC input voltage: 180 - 264 | Efficiency: 85 | Max output current (+12V): 26 | Max output current (+3.3V): 25 | Max output current (+5V): 26 | Max output current (+5Vsb): 2.5 | Max output current (-12V): 0.8 | Power Factor Correction (PFC) type: Active | Power protection features: Overload/Short circuit/Surge protection | Total power: 650 | CPU power connector (4+4 pin): Yes | Motherboard power connector: 24-pin ATX | Number of SATA power connectors: 4 | PCI Express power connectors (6+2 pin): 1 | Peripheral (Molex) power connectors (4-pin): 2 | 80 PLUS certification: No | ATX version: 2.31 | Power supply unit (PSU) form factor: ATX | Purpose: PC | Cooling type: Active | Fan diameter: 120 | Number of fans: 1 | On/off switch: Yes | Product colour: Black | Operating temperature (T-T): 0 - 40 | Storage temperature (T-T): -15 - 40 | Depth: 140 | Height: 86 | Weight: 1000 | Width: 150 | Product Net Weight: 1 | Shipping Box Height: 18 | Unit Calculated Volume: 0.00405 | Unit Calculated Weight: 1.25 | Units per Pallet: 0 | Units per Shipping Box: 8

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950