



Zebra DS9308-SR Fixed bar code reader 1D/2D LED Black



Model: DS9308-SR4U2100AZE

Manufacturer: ZEBRA

EAN:

Product Code: 998523

R3,225

Certification: EN 50581:2012, RoHS 2011/65/EU (2015/863) - EN 50581:2012, IEC 63000, REACH 1907/2006, IEC 62368-1 2nd ed. EN 62368-1:2014/AC:2015, UL/IEC 60950-1, 2nd ed. CAN/CSA C22.2 No.60950-1, 2nd ed. IEC 62471:2006 (Ed.1.0), EN 62471:2008 (LED), FCC 47 CFR Part 15B, ICES-003, EN55032, EN55024, EN55035, VCCI, and SABS | Warnings: Avoid direct contact with eyes. | Warnings: Store away from sources of moisture. | Warnings: The appliance should be disposed of in accordance with local electro-waste regulations. | Type: Fixed bar code reader | Operating temperature (T-T): 0 - 50 °C | Product colour: Black | Storage temperature (T-T): -40 - 70 °C | Connectivity technology: Wired | Weight: 318 g | Power source type: USB | 2D (matrix & stacked) barcodes supported: Micro QR Code | 2D (matrix & stacked) barcodes supported: PDF417 | 2D

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950

(matrix & stacked) barcodes supported: MaxiCode | 2D (matrix & stacked) barcodes supported: QR Code | Input voltage: 5.5 V | Linear (1D) barcodes supported: Code 11 | Linear (1D) barcodes supported: EAN-13 | 2D (matrix & stacked) barcodes supported: Aztec Code | 2D (matrix & stacked) barcodes supported: MicroPDF417 | Linear (1D) barcodes supported: MSI | Linear (1D) barcodes supported: Code 93 | Linear (1D) barcodes supported: U.P.C. | Linear (1D) barcodes supported: Codabar | Linear (1D) barcodes supported: GS1 DataBar | Linear (1D) barcodes supported: Code 39 | Depth: 83 mm | Height: 145 mm | Sensor type: LED | Scanner type: 1D/2D | Pitch reading angle: -60 - 60° | Working distance: 66 cm | International Protection (IP) code: IP52 | Linear (1D) barcodes supported: Code 128 | Optical sensor resolution (W x H): 1280 x 800 pixels | Harmonized System (HS) code: 84716070 | 2D (matrix & stacked) barcodes supported: Data Matrix | 2D (matrix & stacked) barcodes supported: TLC-39 | Power source type: RS-232 | Operating relative humidity (H-H): 5 - 95% | Width: 86 mm | Light levels (direct sunlight): 0 - 107700 lx | 2D (matrix & stacked) barcodes supported: Composite Codes | 2D (matrix & stacked) barcodes supported: Han Xin | 2D (matrix & stacked) barcodes supported: Dot Code A | Standard interfaces: RS-232, USB

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

itworkup.co.za | sales@itworkup.co.za | +27 (11)541-9950